

**Strain Relief Cord Connectors - Steel/Malleable Iron****Applications**

- For use in dry or wet locations to provide a Liquidtight and strain relief termination for flexible cord and cable

Product Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened for a positive Liquidtight seal
- Washers have size range imprinted for identification - eliminates misidentifying inventory
- Use RACO® locknuts and sealing washers to complete a Liquidtight installation on a sheet metal box or panel
- All metallic components are zinc-electroplated for corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for attractive presentation

Bodies

- 3/8" to 1" Steel, 1-1/4" to 1-1/2" Malleable Iron

Nuts

- 3/8" to 1" Steel, 1-1/4" to 1-1/2" Malleable Iron

**Straight Connectors****Straight Connectors - Steel/Malleable Iron**

Catalog #	Cable Range Inches	Unit Carton Qty.	Ship Carton Qty.	Bar Code
1/2" Hubs - Form 1				
3702-1	.125 - .250	—	25	—
3702-2	.250 - .375	—	25	—
3782-2	.250 - .375	1	15	
3702-3	.375 - .425	—	25	—
3702-4	.425 - .500	—	25	—
1/2" Hubs - Form 2				
3702-5	.375 - .500	—	25	—
3782-5	.375 - .500	1	15	
3702-6	.500 - .600	—	25	—
3782-6	.500 - .600	1	15	
3/4" Hubs - Form 3				
3703-1	.250 - .375	—	25	—
3703-2	.375 - .500	—	25	—
3703-3	.500 - .600	—	25	—
3703-4	.600 - .700	—	25	—
3703-6	.650 - .700	—	25	—
3703-5	.700 - .850	—	25	—
1" Hubs - Form 4				
3704-1	.600 - .700	—	25	—
3704-2	.700 - .850	—	25	—
3704-3	.850 - 1.000	—	25	—
1-1/4" Hubs - Form 5				
3705-1	.850 - 1.000	—	25	—
3705-2	1.000 - 1.250	—	25	—
3705-3	1.250 - 1.400	—	25	—
1-1/2" Hubs - Form 6				
3706-1	1.000 - 1.250	—	10	—
3706-2	1.250 - 1.400	—	10	—

See end of section (Pg B109) for detailed drawings »