



1/2 in. Hubs - Form 2 Liquidtight Strain Relief Cord Connector, Cable Range .375 - .500

By Raco
Catalog # 3702-5

1/2 in. Hubs - Form 2 Liquidtight Strain Relief Cord Connector,
Cable Range .375 - .500



*Representative Image

Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for identification - eliminates misidentifying inventory
- Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electroplated for corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- 3/8 in. to 1 in. Steel, 1-1/4 in. to 1-1/2 in. Malleable Iron bodies and nuts
- Additional sizes available

General

Conduit Type	Liquidtight
Connector Type	Strain-Relief
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Connectors
Material	Steel/Malleable Iron
UPC	050169370254

Dimensions

Dimensions	1.469 in x 1.188 in x 1.188 in
Form Size	2 in
Height	1.188 in
Length	1.469 in
Trade Size	1/2 in
Weight	0.178 lb
Width	1.188 in

Conductor Related

Cable Range	0.375 - 0.500 in
-------------	------------------

Certifications And Compliance

Certified Listed	
Hazardous Rating(s)	<ul style="list-style-type: none">• Class I, Division 2• Class II Division 1 & 2• Class III, Division 1 & 2

Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	12000

Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog
Product Logo - LT CORD
SDS - HCC_SDS
Terms and Conditions - HCC Terms & Conditions



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-37025-SPEC-EN | REV 6/2024