

90° Strain Relief Cord Connectors - Steel/Malleable Iron



Applications

- For use in dry or wet locations to provide a Liquidtight and strain relief termination for flexible cord and cable

Product Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened for a positive Liquidtight seal
- Washers have size range imprinted for identification - eliminates misidentifying inventory
- Use RACO® locknuts and sealing washers to complete a Liquidtight installation on a sheet metal box or panel
- All metallic components are zinc-electroplated for corrosion protection

Bodies

- 1/2" to 3/4" Malleable Iron

Nuts

- 1/2" to 3/4" Steel

Compliance

- UL File E195973



90° Connectors

90° Connectors - Malleable Iron

Catalog #	Trade Size	Unit Carton Qty.	Ship Carton Qty.
1/2" Hubs - Form 1			
3792-1	.125 - .250	—	25
3792-2	.250 - .375	—	25
3792-3	.375 - .425	1	25
3792-4	.425 - .500	—	25
1/2" Hubs - Form 2			
3792-5	.375 - .500	—	25
3792-6	.500 - .600	1	25
3/4" Hubs - Form 3			
3793-1	.250 - .375	—	10
3793-2	.375 - .500	—	10
3793-3	.500 - .600	—	10
3793-4	.600 - .650	—	10
3793-6	.650 - .700	—	10
3793-5	.700 - .850	—	10

See end of section (Pg B109) for detailed drawings »