



1/2 in. Hubs - Form 1 90 Degree Liquidtight Strain Relief Cord Connector, Cable Range .425 - .500

By RACO
Catalog # 3792-4

1/2 in. Hubs - Form 1 90 Degree Liquidtight Strain Relief Cord Connector, Cable Range .425 - .500

Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for identification - eliminates misidentifying inventory
- Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electroplated for corrosion protection
- 1/2 in. to 3/4 in. Malleable Iron bodies
- 1/2 in. to 3/4 in. Steel nuts
- Additional sizes available

Specifications

Certified Listed	cULus Listed
Buy American Compliant	Contact Manufacturer
Environmental Conditions	Wet Location
EU RoHS Indicator	Contact Manufacturer
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2
Buy America(n) Qualified	Contact Manufacturer

Conductor

Cable Range	.425 - .500 in
-------------	----------------



Configuration

Connector Type	Strain-Relief
----------------	---------------

Dimensions

Form Size	1 in
Trade Size	1/2 in
Length	1.8 in
Width	1.047 in
Weight	0.216 lb.
Height	1.899 in
Dimensions	1.8 in x 1.047 in x 1.899 in

General

Fitting Type	Connectors
Conduit Type	Liquidtight
Material	Malleable Iron
UPC	050169379240

Logistics

Minimum Pack Quantity	25
Carton Quantity	25
Pallet Quantity	7600

Product Assets

[Catalog \[English\]](#)
[Catalog \[English\]](#)
[Catalog Page \[English\]](#)