



## 3/4 in. Hubs - Form 3 90 Degree Liquidtight Strain Relief Cord Connector, Cable Range .600 - .650

By Raco

Catalog # [3793-4](#)

3/4 in. Hubs - Form 3 90 Degree Liquidtight Strain Relief Cord Connector, Cable Range .600 - .650



\*Representative Image

### Features

- All steel/malleable construction provides mechanical strength
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal
- Washers have size range imprinted for identification - eliminates misidentifying inventory
- Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- All metallic components are zinc electroplated for corrosion protection
- 1/2 in. to 3/4 in. Malleable Iron bodies
- 1/2 in. to 3/4 in. Steel nuts
- Additional sizes available

### General

Catalog Number	3793-4
Conduit Type	Liquidtight
Connector Type	Strain-Relief
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Connectors
Material	Malleable Iron
UPC	050169379349

### Dimensions

Dimensions	2.375 in x 1.204 in x 2.227 in
Form Size	3 in

Height	2.227 in
Length	2.375 in
Trade Size	3/4 in
Weight	0.381 lb
Width	1.204 in

### Conductor Related

Cable Range	.600 - .650 in
-------------	----------------

### Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certified Listed	cULus Listed
Hazardous Rating(s)	<ul style="list-style-type: none"><li>• Class I, Division 2</li><li>• Class II Division 1 &amp; 2</li><li>• Class III, Division 1 &amp; 2</li></ul>

### Logistics

Carton Quantity	10
Minimum Pack Quantity	10
Pallet Quantity	4800

### Product Assets

<a href="#">Catalogs - RACO / TayMac / Bell Full Catalog</a>
<a href="#">Catalogs - Commercial Fittings</a>
<a href="#">Product Logo - LT CORD</a>
<a href="#">SDS - HCC SDS</a>
<a href="#">Specifications - 37934</a>
<a href="#">Terms and Conditions - HCC Terms &amp; Conditions</a>



A Hubbell brand