



# 1/2 in. Hubs Form 1 Liquidtight Strain Relief Connector, Cable Range .312 - .375

By Raco  
Catalog # 4801-4

1/2 in. Hubs Form 1 Liquidtight Strain Relief Connector, Cable Range .312 - .375



\*Representative Image

### Features

- Aluminum construction provides a corrosion resistant installation
- Innovative GOTHCA® ring incorporates a split hinge design to prevent friction and to provide strain relief
- Neoprene grommet
- Knurled compression nut allows the fittings to be hand tightened to UL requirements
- GOTCHA® color-coded ring provides fast identification of cord size
- Additional colors and sizes available

### General

Color Code	White
Conduit Type	Liquidtight
Connector Type	Strain-Relief
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Connectors
Material	Aluminum
UPC	050169480144

### Dimensions

Dimensions	0.88 in x 1.36 in x 1.36 in
Form Size	1 in
Height	1.36 in
Length	0.88 in
Trade Size	1/2 in
Weight	0.059 lb
Width	1.36 in

### Conductor Related

Cable Range	.312 - .375 in
-------------	----------------

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
Hazardous Rating(s)	<ul style="list-style-type: none"><li>• Class I, Division 2</li><li>• Class II Division 1 &amp; 2</li><li>• Class III, Division 1 &amp; 2</li></ul>
Industry Standard(s)	UL 514B

### Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	12000

### Product Assets

Catalogs - [RACO / TayMac / Bell Full Catalog](#)  
Literature - [Raco\\_Liquidtight\\_Diameter\\_Range\\_B60](#)  
Product Logo - [LT CORD](#)  
SDS - [HCC\\_SDS](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A proud member of the Hubbell Family.