



## Two Device Handy / Switch Boxes and Covers

### Applications

- Installers can save time and cut installation costs with two gang switch boxes
- Larger capacity boxes are ideal for today's designs where there is a need to install two devices at one location
- Drawn boxes are ideal for exposed work applications (surface mounted wiring)

### Product Features

- 681, 685 bracketed boxes are set back 1/2" eliminating the need for a plaster ring
- Reference the Box Selection section in the front of this catalog for complete description of bracket and clamp types and features
- 871, 872 and 873 covers are unpainted and manufactured from pre-galvanized steel

### Compliance

- **UL LISTED**
  - All RACO UL listed steel boxes are acceptable for use in 2 hr. fire rated floor-ceiling and roof-ceiling assemblies, as well as 2 hr. fire rated bearing and non-bearing wood stud and steel stud walls.
- For additional information consult Fire Resistance Ratings ANSI/UL 263, Sec. III-6



### 4" Square Two Devices Boxes and Plates

| Cat. #                                             | Description              | Cubic Inches (CM³) | Knockouts             |                       | Std. Pkg. | Bar Code |
|----------------------------------------------------|--------------------------|--------------------|-----------------------|-----------------------|-----------|----------|
|                                                    |                          |                    | Sides Conduit         | Bottom Conduit        |           |          |
| Switch Boxes, 2-1/8" Deep - Drawn with Conduit KOs |                          |                    |                       |                       |           |          |
| 680                                                | —                        | 30.3<br>(496.5)    | (12) 1/2"             | (5) 1/2"              | 25        |          |
| 683                                                | —                        | 30.3<br>(496.5)    | (8) 1/2",<br>(4) 3/4" | (3) 1/2",<br>(2) 3/4" | 25        |          |
| 683SP                                              | —                        | 30.3<br>(496.5)    | (8) 1/2",<br>(4) 3/4" | (3) 1/2",<br>(2) 3/4" | 10        |          |
| 681                                                | TS Bracket, 1/2" Setback | 30.3<br>(496.5)    | (9) 1/2"              | (5) 1/2"              | 25        |          |
| 681SP                                              | TS Bracket, 1/2" Setback | 30.3<br>(496.5)    | (9) 1/2"              | (5) 1/2"              | 8         |          |
| 685                                                | TS Bracket, 1/2" Setback | 30.3<br>(496.5)    | (6) 3/4"              | (3) 1/2",<br>(2) 3/4" | 25        |          |
| 685SP                                              | TS Bracket, 1/2" Setback | 30.3<br>(496.5)    | (6) 3/4"              | (3) 1/2",<br>(2) 3/4" | 8         |          |

### Wall Plates

|            |                                                        |   |   |   |    |  |
|------------|--------------------------------------------------------|---|---|---|----|--|
| <b>871</b> | 2 Toggle Switches, 1/4" Raised from Surface            | — | — | — | 25 |  |
| <b>872</b> | 1 Duplex and 1 Toggle Switch, 1/4" Raised from Surface | — | — | — | 25 |  |
| <b>873</b> | 2 Duplex Receptacles, 1/4" Raised from Surface         | — | — | — | 25 |  |

See end of section (Pg A91) for detailed drawings »