

# Stainless steel fittings

## Couplings

### COUPLINGS

UL File No. E-324286



RC50 304SS



#### Features:

- Designed for use with stainless threaded rigid conduit
- These stainless steel couplings are polished to a bright finish for increased corrosion resistance and improved appearance

| Cat. #      | Size   | Unit qty. | Std. pkg. | Wt. lbs. per 100 | Length | Outside dia. |
|-------------|--------|-----------|-----------|------------------|--------|--------------|
| RC50 304SS  | 1/2"   | 1         | 1         | 18               | 1.625" | 1.01"        |
| RC75 304SS  | 3/4"   | 1         | 1         | 26               | 1.650" | 1.25"        |
| RC100 304SS | 1"     | 1         | 1         | 28               | 2.000" | 1.53"        |
| RC125 304SS | 1 1/4" | 1         | 1         | 41               | 2.040" | 1.95"        |
| RC150 304SS | 1 1/2" | 1         | 1         | 51               | 2.063" | 2.16"        |
| RC200 304SS | 2"     | 1         | 1         | 69               | 2.125" | 2.65"        |
| RC250 304SS | 2 1/2" | 1         | 1         | 178              | 3.188" | 3.25"        |
| RC300 304SS | 3"     | 1         | 1         | 229              | 3.313" | 3.87"        |
| RC400 304SS | 4"     | 1         | 1         | 313              | 3.516" | 4.88"        |
| RC50 316SS  | 1/2"   | 1         | 1         | 18               | 1.625" | 1.01"        |
| RC75 316SS  | 3/4"   | 1         | 1         | 26               | 1.650" | 1.25"        |
| RC100 316SS | 1"     | 1         | 1         | 28               | 2.000" | 1.53"        |
| RC125 316SS | 1 1/4" | 1         | 1         | 41               | 2.040" | 1.95"        |
| RC150 316SS | 1 1/2" | 1         | 1         | 51               | 2.063" | 2.16"        |
| RC200 316SS | 2"     | 1         | 1         | 69               | 2.125" | 2.65"        |
| RC250 316SS | 2 1/2" | 1         | 1         | 178              | 3.188" | 3.25"        |
| RC300 316SS | 3"     | 1         | 1         | 229              | 3.313" | 3.87"        |
| RC400 316SS | 4"     | 1         | 1         | 313              | 3.516" | 4.88"        |

### THREE-PIECE COUPLINGS



191SS

#### Features:

- Designed to join and connect threaded ends of rigid conduit where neither length of conduit can be turned
- These stainless steel three-piece couplings are polished to a bright finish for increased corrosion resistance and improved appearance
- 316 stainless steel

| Cat. # | Size | Unit qty. | Std. pkg. | Wt. lbs. per 100 | Overall length | Major nut dia. | Major body dia. |
|--------|------|-----------|-----------|------------------|----------------|----------------|-----------------|
| 191SS  | 3/4" | 50        | 50        | 33               | 1.51"          | 1.51"          | 1.31"           |
| 192SS  | 1"   | 50        | 50        | 33               | 1.51"          | 1.66"          | 1.66"           |

Stainless steel