



Rittal – The System.

Faster – better – everywhere.



VX 8100.733

Punched section with mounting flange, 23 x 89 mm, stainless steel

State: 31/12/2024 (Source: rittal.com/com-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



VX 8100.733 - Punched section with mounting flange, 23 x 89 mm, stainless steel for VX, VX SE

For variable, individual interior installation of the enclosure frame on the inner mounting level.

Features

Model No.	VX 8100.733
Product description	For variable, individual interior installation of the enclosure frame on the inner mounting level.
Benefits	Simply locate into the system punchings and screw-fasten System punchings on all four sides With slots at the top and bottom for cage nuts, for attaching your own components via metric screws Especially for cable routing in the VX base/plinth, stainless steel and for the installation of busbar supports (non-magnetic stainless steel).
Material	Stainless steel 1.4301 (AISI 304)
Supply includes	Assembly parts
Installation options	In VX on the inner mounting level, on the VX enclosure section In VX SE, on the enclosure section in conjunction with VX adaptor rail On identical punched sections with mounting flanges Base/plinth system VX, stainless steel, in the width and depth, combined with a base/plinth installation bracket
To fit	Enclosure type: VX VX SE To fit width/depth: 800 mm
Packs of	2 pc(s).
Net weight	1.788
Gross weight	2.02
Customs tariff number	73269098
EAN	4028177924529

Features

ETIM 9	EC002620
ECLASS 8.0	27189234