



undefined 9982.500

HD Disconnect Modules

State: 4/23/2026 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE



SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



undefined 9982.500 - HD Disconnect Modules

Installs on the lock side of a single door HD enclosure. Compatible with most operator handles.



Features

Model No.	9982.500
Version	Roof slope 30° towards the front
Material	Housing: Stainless steel 1.4301 (AISI 304) Seal: Silicone, compliant with FDA Guideline 21 CFR 177.2600 Interconnecting hardware: Zinc plated
Surface finish	Housing: Brushed, grain 400, peak-to-valley height < 0.8 µm Seal: Blue, dyed (RAL 5010)
Supply includes	Disconnect module Hardware for installation to HD enclosure Disconnect interconnecting hardware Connector bar for 15/20/40/42 high enclosures Connector bar for 24 high enclosures
Note	Installs on the left side of the HD enclosure
Dimensions	Depth: 150 mm Depth: 5.91 "
Protection category IP to IEC 60529	IP 66
Protection category NEMA	NEMA 4X
Type rating according to UL 50E	Type 4X
Packaging unit	1 pc(s).
Customs tariff number	9403999040

Approvals

Approvals

UL