

PVC Coated ST Style Knockout Hub

1 INCH STG KNOCKOUT HUB W/ GROUND

ISO

9001:2015

CERTIFIED

Catalog NumberPRSTG3

UPC784011207503

Description

PVC coated STG knockout hubs with grounding lug are used to terminate conduit runs through the wall of a sheet metal electrical enclosure.

Application

- Used to terminate conduit runs through the wall of a sheet metal electrical enclosure


Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- Available in 12 trade sizes from 1/2" through 6"
- Sealing sleeves on conduit side of hub
- Molded PVC gasket seals flush with enclosure wall
- O-ring gasket provides additional seal
- Furnished with a grounding lug

General Information

Trade Size	1
Material	FERROUS METAL
Material	FERROUS METAL
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane
Seal Type	O-ring gasket
Grounding Lug	Attached

Dimensions



Dimension A (Inches) 1.66

Dimension B (Inches) 2.5

Dimension C (Inches) 1.03

Max Wall Thickness (Inches) .25

Nominal Weight (Pounds) 0.4

Standards

NEC/CEC Class II, Division 1 & 2

NEC/CEC Class III, Division 1 & 2

NEC/CEC Class I, Division 2

Technical Specification Documents

Specification Guide (1995 Master) AVAILABLE ON WEBSITE

Specification Guide (2004 Master) AVAILABLE ON WEBSITE

Installer Certification and Tools AVAILABLE ON WEBSITE

Chemical Resistance Charts AVAILABLE ON WEBSITE

Performance Specifications AVAILABLE ON WEBSITE

Technical Information

Conduit Body STG

Fitting Type KNOCKOUT HUB

Product Category FITTING

Product Family PVC Coated ST Style Knockout Hub



Notes

- All Screw-tight Hubs are listed for NEMA and UL type enclosures 2, 3, 3R, 4, 4x, 11 and 12
- Grounding and Bonding Hubs are listed for NEMA Enclosures 2, 3, 3R, 4 and