

PVC Coated ST Style Knockout Hub

1-1/4 INCH STG KNOCKOUT HUB W/ GROUND



Catalog NumberPRSTG4

UPC784011207510

Description

PVC coated STG knockout hubs with grounding lug are used to terminate conduit runs through the wall of a sheet metal electrical enclosure.

Application

- Used to terminate conduit runs through the wall of a sheet metal electrical enclosure


Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- Available in 12 trade sizes from 1/2" through 6"
- Sealing sleeves on conduit side of hub
- Molded PVC gasket seals flush with enclosure wall
- O-ring gasket provides additional seal
- Furnished with a grounding lug

General Information

Trade Size	1-1/4
Material	FERROUS METAL
Material	FERROUS METAL
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane
Seal Type	O-ring gasket
Grounding Lug	Attached

Dimensions



Dimension A (Inches) 1.69

Dimension B (Inches) 3.25

Dimension C (Inches) 1.03

Max Wall Thickness (Inches) .25

Nominal Weight (Pounds) 0.4

Standards

NEC/CEC	Class I, Division 2
NEC/CEC	Class II, Division 1 & 2
NEC/CEC	Class III, Division 1 & 2

Technical Specification Documents

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

Technical Information

Conduit Body	STG
Fitting Type	KNOCKOUT HUB
Product Category	FITTING
Product Family	PVC Coated ST Style Knockout Hub

Notes

- All Screw-tight Hubs are listed for NEMA and UL type enclosures 2, 3, 3R, 4, 4x, 11 and 12
- Grounding and Bonding Hubs are listed for NEMA Enclosures 2, 3, 3R, 4 and

