

Conduit Unions UNF & UNY Unions

1/2 INCH FEMALE-TO-FEMALE (F/F) UNF UNION



Catalog Number PRUNF105
UPC 784011207701

Description

PVC coated UNF unions are used to connect conduit to conduit or to allow for future changes to the conduit system. Female threads are provided at each end.

Application

- Applicable for Hazardous Locations

Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings
- Molded PVC gasket seals fitting


General Information

| | |
|-----------------|---|
| Trade Size | 1/2 |
| Material | FERROUS METAL |
| Material | FERROUS METAL |
| Exterior Finish | A nominal .040 inch (40 mil) gray PVC coating |
| Interior Finish | A nominal .002 inch (2 mil) red urethane |

Dimensions

| | |
|-------------------------|------|
| Length (Inches) | 1.81 |
| Max Diameter (Inches) | 2 |
| Nominal Weight (Pounds) | 0.3 |

Standards



| | |
|---------|--|
| CSA | C22.2 No. 30 |
| NEC/CEC | Class III |
| NEC/CEC | Class II, Division 2, Groups F, G |
| NEC/CEC | Class II, Division 1, Groups E, F, G |
| NEC/CEC | Class I, Division 1 & 2, Groups A, B, C, D |
| UL 1203 | E476062 |

Technical Specification Documents

| | |
|-----------------------------------|----------------------|
| Specification Guide (1995 Master) | AVAILABLE ON WEBSITE |
| Specification Guide (2004 Master) | AVAILABLE ON WEBSITE |
| Installer Certification and Tools | AVAILABLE ON WEBSITE |
| Chemical Resistance Charts | AVAILABLE ON WEBSITE |
| Performance Specifications | AVAILABLE ON WEBSITE |

Technical Information

| | |
|-----------------------|---------------------------------|
| Fitting Configuration | F/F |
| Fitting Type | UNION |
| Product Category | HAZARDOUS LOCATION FITTING |
| Product Family | Conduit Unions UNF & UNY Unions |
| Rating | Hazardous Location |

