

# Product data sheet

Specifications



30mm Push Button, Types K, SK or KX, light module, blue LED lamp, 24/28 VAC/VDC

9001KM35LL

Product availability: Non-Stock - Not normally stocked in distribution facility

## Main

|                           |                                        |
|---------------------------|----------------------------------------|
| Range of Product          | Harmony 9001K<br>Harmony 9001SK        |
| Product or Component Type | Light module<br>Light block            |
| Device short name         | 9001K                                  |
| Bulb base                 | BA 9s                                  |
| Light block supply        | Direct via integral resistance 0.28 VA |

## Complementary

|                           |                                         |
|---------------------------|-----------------------------------------|
| Light source              | LED (bulb included)                     |
| Light block colour        | Blue                                    |
| [Us] rated supply voltage | 24...28 V AC 50...60 Hz<br>24...28 V DC |

## Environment

|                                       |                                                                                                                |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TC                                                                                                             |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)<br>-40...158 °F (-40...70 °C)                                                       |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)<br>-13...158 °F (-25...70 °C)                                                       |
| IP degree of protection               | IP10 IEC 60529                                                                                                 |
| Standards                             | UL 508<br>CSA C22.2 No 14<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>JIS C 4520<br>JIS C 852 |
| Product Certifications                | UL Listed<br>CSA<br>NEMA                                                                                       |
| Electrical shock protection class     | Class II conforming to IEC 61140                                                                               |
| Vibration resistance                  | 7 gn (f= 2...500 Hz) conforming to IEC 60068-2-6                                                               |
| Shock resistance                      | 50 gn IEC 60068-2-27                                                                                           |

## Ordering and shipping details

|                   |              |
|-------------------|--------------|
| Category          | US10CS121435 |
| Discount Schedule | 0CS1         |
| GTIN              | 785901474807 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                   |    |
|-------------------|----|
| Returnability     | No |
| Country of origin | MX |

## Packing Units

|                        |                       |
|------------------------|-----------------------|
| Unit Type of Package 1 | PCE                   |
| Nbr. of units in pkg.  | 1                     |
| Package 1 Height       | 5.080 in (12.903 cm)  |
| Package 1 Width        | 2.00 in (5.08 cm)     |
| Package 1 Length       | 12.903 in (32.774 cm) |
| Package weight(Lbs)    | 2.400 oz (68.039 g)   |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

SCIP Number

Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

California proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.