

Product data sheet

Specifications



Pilot light, Harmony 9001K, metal, polycarbonate, fresnel lens, green, 30mm, 120VAC

9001KP1G31

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product Harmony 9001K

Product or Component Type Pilot light

Device short name K

Complementary

Bezel material Metal

Mounting diameter 1.2 in (30 mm)

Lens type Fresnel plastic

Cap/operator or lens colour Green

Light source incandescent

Bulb base BA 9s

Light block supply Via transformer 120 V AC 50/60 Hz
Via integral transformer 110 V AC 50/60 Hz

Connections - terminals Screw clamp terminals, 1 x 0.22...2 x 1.5 mm² IEC 60947-1

Shape of screw head Round

Operating position Any position

Light source Incandescent bulb

[Us] rated supply voltage 110...120 V AC

Operating Mode Normal

Device presentation Complete product

Lens type Fresnel

[Us] rated supply voltage 110...120 V

Light block supply Via integral transformer

Supply frequency 50...60 Hz

Lens material Polycarbonate

Size 30 mm

Environment

Product Certifications CSA LR25490 class 3211 03
UL listed file E42259 CCN NKCR
CE

NEMA degree of protection NEMA 1/2/3/3R/4/6/12/13

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	US10CS121426
Discount Schedule	0CS1
GTIN	3389118041462
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.77 in (4.500 cm)
Package 1 Width	2.17 in (5.500 cm)
Package 1 Length	3.54 in (9.000 cm)
Package weight(Lbs)	8.078 oz (229.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	35
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	18.243 lb(US) (8.275 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	560
Package 3 Height	29.53 in (75.000 cm)
Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	307.942 lb(US) (139.680 kg)

Contractual warranty

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Offer Marketing Illustration

Product benefits / Features

Features

Harmony 9001K



- 

Improved security thanks to finger-safe contact blocks and light modules
- 

Single screw Contact Block Fastening
- 

Robustness to withstand the harshest environments
- 

Large metal set of accessories to customize your product
- 

Automatic self-grounding operators without additional wiring

Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony 9001K



Image of product / Alternate images

Alternative



