

Product data sheet

Characteristics

9001KR3BH5

Push-button, Harmony 9001K, metal, projecting, black, 30mm, spring return, 1 NO



Main

| | |
|---------------------------------|------------------|
| Range of Product | Harmony 9001K |
| Product or Component Type | Push-button |
| Device short name | K |
| Type of operator | Spring return |
| Operator profile | Black projecting |
| Operator additional information | Without guard |

Complementary

| | |
|--------------------------------|----------------------------|
| Bezel material | Metal |
| Mounting diameter | 1.2 in (30 mm) |
| Light source | without |
| Light source | Without |
| Light block supply | Without supply |
| Contacts type and composition | 1 NO |
| Connections - terminals | Screw clamp terminals |
| Operating position | Any position |
| [Ie] rated operational current | 10 A, AC-15 10 A, DC-13 |
| Contact operation | Standard |
| Device presentation | Complete product |
| Cap/operator or lens colour | Black |
| Operator profile | Projecting |
| Type of operator | Spring return |
| Size | 30 mm |

Environment

| | |
|---------------------------|--|
| Product Certifications | NEMA[RETURN]UL listed file E42259 CCN NKCR[RETURN]CE[RETURN]CSA LR 25490 class 3211 03 |
| NEMA degree of protection | NEMA 1/2/3/3R/4/6/12/13 |

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10CS121426 |
| Discount Schedule | OCS1 |
| GTIN | 785901033721 |
| Returnability | Yes |
| Country of origin | MX |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.900 in (4.826 cm) |
| Package 1 Width | 3.700 in (9.398 cm) |
| Package 1 Length | 2.200 in (5.588 cm) |
| Package 1 Weight | 4.160 oz (117.934 g) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|