

Product data sheet

Specifications



CONTROL STATION + OPERATORS

9001KYSK111

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	Harmony 9001KY
Product or Component Type	Control station
Device short name	9001KY
Provided equipment	Label plate HAND-OFF-AUTO
Contact block name	KA1
Product Specific Application	For hoisting and mechanical handling applications
Level or class	Class II Division 2 Group G Class III

Complementary

Enclosure/cubicle description	Wall-mounted enclosure 1 cut-out Ø 30 mm
AC control voltage 50 HZ	125...600 V
Enclosure material	Stainless Steel
Type of Installation	Indoor/outdoor
Control station composition	1 selector switch 1 NO/1 NC
AC control voltage 60 HZ	125...600 V
Mechanical interlocking	Without mechanical interlock
DC control voltage	125...600 V
Connector Type	Screw clamp connector
Connections - terminals	Direct connection AWG 2) solid stranded Direct connection AWG 12) solid stranded Direct connection AWG 24) solid stranded
[Ue] rated operational voltage	300 V
[Ie] rated operational current AC	10 A
Number of command positions	1
Number of indicator lights	0
Number of push buttons	0
Number of selector switches	1
Number of key switches	0
Number of mushroom-shaped push-buttons	0
Emergency Power Off (EPO)	No
Number of contacts as normally closed contact	0
Number of contacts as normally open contact	0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of contacts as change-over contact	0
Housing material	Metal
Housing Colour	Grey
colour of cover	Grey

Environment

NEMA Degree of Protection	NEMA 4X/13
Environmental characteristic	Resistant against immersion in water Dust and oil resistant
Product Certifications	UL Listed
Ambient Air Temperature for Operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
IP Degree of Protection	IP66

Ordering and shipping details

Category	US10CS121426
Discount Schedule	0CS1
GTIN	785901040071
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	12.700 in (32.258 cm)
Package 1 Width	5.0 in (12.7 cm)
Package 1 Length	32.258 in (81.935 cm)
Package weight(Lbs)	2.650 lb(US) (1.202 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

California proposition 65

WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Take-back

No