

Product data sheet

Specifications



Illuminated push-button head,
Harmony 9001SK, plastic, plastic
guard flush, green, 30mm, spring
return, 110-120V

9001SK1L1G

Product availability: Non-Stock - Not normally stocked in
distribution facility

Main

Range of Product	Harmony 9001SK
Product or Component Type	Head for illuminated push-button
Device short name	9001SK

Complementary

Bezel material	Plastic
Mounting diameter	1.2 in (30 mm)
Shape of signaling unit head	Octagonal
Operator additional information	Plastic guard
Bulb base	BA 9s
Light block supply	Via transformer 120 V AC 50/60 Hz
Contacts type and composition	Without contact block
Product Certifications	CE UL listed file E42259 CCN NKCR CSA LR24590 class 3211 03
IP degree of protection	IP64
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13
Cap/operator or lens colour	Green
[Us] rated supply voltage	110...120 V
Light block supply	Via integral transformer
Operator profile	Flush
Type of operator	Spring return
Supply frequency	50...60 Hz
Size	30 mm
Light source	Incandescent bulb

Ordering and shipping details

Category	US10CS121429
Discount Schedule	0CS1
GTIN	785901820932
Returnability	Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin	MX
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	2.21 in (5.601 cm)
------------------	--------------------

Package 1 Width	3.66 in (9.299 cm)
-----------------	--------------------

Package 1 Length	1.81 in (4.600 cm)
------------------	--------------------

Package weight(Lbs)	6.561 oz (186.000 g)
---------------------	----------------------

Unit Type of Package 2	S01
------------------------	-----

Number of Units in Package 2	8
------------------------------	---

Package 2 Height	5.91 in (15 cm)
------------------	-----------------

Package 2 Width	5.91 in (15 cm)
-----------------	-----------------

Package 2 Length	15.75 in (40 cm)
------------------	------------------

Package 2 Weight	3.640 lb(US) (1.651 kg)
------------------	-------------------------

Unit Type of Package 3	P06
------------------------	-----

Number of Units in Package 3	256
------------------------------	-----

Package 3 Height	29.53 in (75.000 cm)
------------------	----------------------

Package 3 Width	31.50 in (80.000 cm)
-----------------	----------------------

Package 3 Length	23.62 in (60.000 cm)
------------------	----------------------

Package 3 Weight	134.125 lb(US) (60.838 kg)
------------------	----------------------------

Contractual warranty

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.