

Selector switch head, Harmony 9001SK, plastic, standard handle, black, 30mm, 3 positions, spring return left to center

9001SKS63B

Product availability: Non-Stock - Not normally stocked in distribution facility

### Main

Range of Product	Harmony 9001SK	
Product or Component Type	Head for selector switch	
Device short name	9001SK	

## Complementary

Bezel material	Plastic
Mounting diameter	1.2 in (30 mm)
Operator position information	3 positions
Contacts type and composition	Without contact block
Device presentation	Basic element
Cap/operator or lens colour	Black
Operator profile	Standard handle
Type of operator	Spring return
Size	30 mm
Return	Left to centre
Cam profile	3

## **Environment**

Protective treatment	TC	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)	
Electrical shock protection class	Class II conforming to IEC 61140	
IP degree of protection	IP66 IEC 60529	
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13	
Product Certifications	CSA LR24590 class 3211 03 CE UL listed file E42259 CCN NKCR	

# Ordering and shipping details

Category	US10CS121429
Discount Schedule	0CS1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

GTIN	785901044109	
Returnability	Yes	
Country of origin	MX	

# **Packing Units**

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	1.81 in (4.600 cm)	
Package 1 Width	2.17 in (5.500 cm)	
Package 1 Length	3.90 in (9.900 cm)	
Package weight(Lbs)	2.081 oz (59.000 g)	
Unit Type of Package 2	S01	
Number of Units in Package 2	14	
Package 2 Height	5.91 in (15.000 cm)	
Package 2 Width	5.91 in (15.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	2.262 lb(US) (1.026 kg)	
Unit Type of Package 3	P06	
Number of Units in Package 3	448	
Package 3 Height	29.53 in (75.000 cm)	
Package 3 Width	23.62 in (60.000 cm)	
Package 3 Length	31.50 in (80.000 cm)	
Package 3 Weight	90.019 lb(US) (40.832 kg)	

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

## Environmental footprint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

## **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.