

# Product data sheet

Specifications



Push-to-test pilot light head,  
Harmony 9001SK, plastic, without  
cap, 30mm, LED red, 24-28V

9001SKT35LR

**Product availability:** Non-Stock - Not normally stocked in  
distribution facility

## Main

|                           |                                   |
|---------------------------|-----------------------------------|
| Range of Product          | Harmony 9001SK                    |
| Product or Component Type | Head for push-to-test pilot light |
| Device short name         | 9001SK                            |
| Light block supply        | Direct 24...28 V AC/DC            |

## Complementary

|                                             |                                                           |
|---------------------------------------------|-----------------------------------------------------------|
| Bezel material                              | Plastic                                                   |
| Mounting diameter                           | 1.2 in (30 mm)                                            |
| Shape of signaling unit head                | Round                                                     |
| Cap/operator or lens colour                 | Without cap                                               |
| Light source                                | Red LED                                                   |
| Bulb base                                   | BA 9s                                                     |
| [Us] rated supply voltage                   | 24...28 V AC/DC                                           |
| Tightening torque                           | 7.08 lbf.in (0.8 N.m) IEC 60947-1                         |
| Shape of screw head                         | Cross slotted                                             |
| Connections - terminals                     | Screw clamp terminals, 1 x 0.22...2 x 1.5 mm² IEC 60947-1 |
| [Ith] conventional free air thermal current | 10 A                                                      |
| Short-circuit protection                    | 10 A cartridge fuse IEC 60947-5-1                         |
| [Ui] rated insulation voltage               | 250 V 2)IEC 60947-1                                       |
| [Uimp] rated impulse withstand voltage      | 2.5 kV IEC 60947-1                                        |
| Operating position                          | Any position                                              |
| Operating Mode                              | Push-to-test                                              |
| CAD overall width                           | 2.1 in (54 mm)                                            |
| CAD overall height                          | 2.8 in (70 mm)                                            |
| CAD overall depth                           | 1.7 in (42 mm)                                            |
| Product Weight                              | 0.399 lb(US) (0.181 kg)                                   |
| [Us] rated supply voltage                   | 24...28 V                                                 |
| Light source colour                         | Red                                                       |
| Contacts type and composition               | 1 C/O                                                     |
| Size                                        | 30 mm                                                     |
| Light source                                | LED                                                       |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

|                                       |                                                                                                                         |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Electrical shock protection class     | Class II conforming to IEC 61140                                                                                        |
| Protective treatment                  | TC                                                                                                                      |
| IP Degree of Protection               | IP65/IP66                                                                                                               |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X                                        |
| Vibration resistance                  | 7 gn (f= 2...500 Hz) conforming to IEC 60068-2-6                                                                        |
| Shock resistance                      | 50 gn IEC 60068-2-27                                                                                                    |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)                                                                                              |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)                                                                                              |
| Standards                             | JIS C8201-5-1<br>IEC 60947-5-4<br>CSA C22.2 No 14<br>IEC 60947-5-1<br>IEC 60947-1<br>JIS C 852<br>UL 508<br>JIS C8201-1 |
| Product Certifications                | UL 508<br>NEMA                                                                                                          |

## Ordering and shipping details

|                   |              |
|-------------------|--------------|
| Category          | US10CS121429 |
| Discount Schedule | 0CS1         |
| GTIN              | 785901447818 |
| Returnability     | No           |
| Country of origin | MX           |

## Packing Units

|                        |                       |
|------------------------|-----------------------|
| Unit Type of Package 1 | PCE                   |
| Nbr. of units in pkg.  | 1                     |
| Package 1 Height       | 5.080 in (12.903 cm)  |
| Package 1 Width        | 2.00 in (5.08 cm)     |
| Package 1 Length       | 12.903 in (32.774 cm) |
| Package weight(Lbs)    | 8.000 oz (226.796 g)  |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

California proposition 65

WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Take-back

No