

# Product data sheet

Specifications



## connection sub-base ABE7 - for distribution of 4 analog output channels

ABE7CPA21

**Product availability: Stock - Normally stocked in distribution facility**

### Main

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of Product          | Modicon ABE7                                                                                                                                                                                                                                                                                                                                                                                                             |
| Product or Component Type | Connection sub-base for counter and analogue channels                                                                                                                                                                                                                                                                                                                                                                    |
| Number of channels        | 4                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Connections - terminals   | Screw type terminals, 1 x 0.09...1 x 1.5 mm² AWG 28...AWG 16) flexible with cable end<br>Screw type terminals, 1 x 0.14...1 x 2.5 mm² AWG 26...AWG 12) solid<br>Screw type terminals, 1 x 0.14...1 x 2.5 mm² AWG 26...AWG 14) flexible without cable end<br>Screw type terminals, 2 x 0.09...2 x 0.75 mm² AWG 28...AWG 20) flexible with cable end<br>Screw type terminals, 2 x 0.2...2 x 2.5 mm² AWG 24...AWG 14) solid |

### Complementary

|                               |                                                                                  |
|-------------------------------|----------------------------------------------------------------------------------|
| Function of module            | Analogue output current Premium<br>Analogue output voltage Premium               |
| Product compatibility         | Premium TSXAEY420<br>Premium TSXASY410                                           |
| Connection to PLC             | SUB-D 25                                                                         |
| Fixing mode                   | By clips (35 mm symmetrical DIN rail)<br>By screws (solid plate with fixing kit) |
| [Ui] rated insulation voltage | 2000 V terminals/mounting rails                                                  |
| Installation category         | II IEC 60664-1                                                                   |
| Tightening torque             | 5.3 lbf.in (0.6 N.m) flat Ø 3.5 mm                                               |
| Product Weight                | 0.40 lb(US) (0.18 kg)                                                            |

### Environment

|                                       |                                                                        |
|---------------------------------------|------------------------------------------------------------------------|
| Product Certifications                | DNV<br>GL<br>CSA<br>UL<br>EAC                                          |
| IP degree of protection               | IP20 conforming to IEC 60529                                           |
| Protective treatment                  | TC                                                                     |
| Resistance to incandescent wire       | 1382 °F (750 °C) 30 s IEC 60695-2-11                                   |
| Shock resistance                      | 15 gn 11 ms IEC 60068-2-27                                             |
| Vibration resistance                  | 2 gn (f= 10...150 Hz) conforming to IEC 60068-2-6                      |
| Resistance to electrostatic discharge | 4 kV contact) level 3 IEC 61000-4-2<br>8 kV air) level 3 IEC 61000-4-2 |
| Resistance to radiated fields         | 9.1 V/m (10 V/m) 26000000...1000000000 Hz)IEC 61000-4-3 level 3        |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                       |                                        |
|---------------------------------------|----------------------------------------|
| Resistance to fast transients         | 2 kV level 3 IEC 61000-4-4             |
| Ambient air temperature for operation | 32...140 °F (0...60 °C) IEC 61131-2    |
| Ambient air temperature for storage   | -40...176 °F (-40...80 °C) IEC 61131-2 |
| Pollution degree                      | 2 IEC 60664-1                          |

## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10CP222375  |
| Discount Schedule | 0CP2          |
| GTIN              | 3389110836196 |
| Returnability     | Yes           |
| Country of origin | LV            |

## Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Nbr. of units in pkg.        | 1                        |
| Package 1 Height             | 2.756 in (7.000 cm)      |
| Package 1 Width              | 3.268 in (8.300 cm)      |
| Package 1 Length             | 3.780 in (9.600 cm)      |
| Package weight(Lbs)          | 7.690 oz (218.000 g)     |
| Unit Type of Package 2       | S03                      |
| Number of Units in Package 2 | 36                       |
| Package 2 Height             | 11.811 in (30.000 cm)    |
| Package 2 Width              | 11.811 in (30.000 cm)    |
| Package 2 Length             | 15.748 in (40.000 cm)    |
| Package 2 Weight             | 18.409 lb(US) (8.350 kg) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                |
|--------------------------------------------------------|----------------|
| Total lifecycle Carbon footprint                       | 55 kg CO2 eq.  |
| Carbon footprint of the manufacturing phase [A1 to A3] | 6 kg CO2 eq.   |
| Carbon footprint of the distribution phase [A4]        | 0 kg CO2 eq.   |
| Carbon footprint of the installation phase [A5]        | 0.1 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 49 kg CO2 eq.  |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.5 kg CO2 eq. |

## Use Better



### Materials and Substances

|                                        |                                                                                                                                                                                                                                                                                                    |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                                                                                                                                                                                                                                |
| Packaging without single use plastic   | Yes                                                                                                                                                                                                                                                                                                |
| SCIP Number                            | 11b66df7-80cd-4614-acd8-17183a716ce1                                                                                                                                                                                                                                                               |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                                                                                                                                                                                                                             |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a>                                                                                                                                                                                                             |
| California proposition 65              | <b>WARNING:</b> This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again




### Repack and remanufacture

|                               |                                                                                                                                                                                                                  |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in % | 6                                                                                                                                                                                                                |
| Circularity Profile           | <a href="#">End of Life Information</a>                                                                                                                                                                          |
| Take-back                     | No                                                                                                                                                                                                               |
| WEEE Label                    |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Dimensions Drawings

Dimensions


mm  
in.



(1) ABE7BV20


Mounting and Clearance

Mounting



Connections and Schema

Wiring Recommendations



- (1) 4 input voltage - 4 output voltage
- (2) 4 input current - 4 output current
- (3) Channel via 1
- (4) Channel via 2

Image of product / Alternate images

Alternative

---

