

# Product data sheet

Specifications



## switch module, Modicon X80, network option switch

BMENOS0300

**Product availability: Non-Stock - Not normally stocked in distribution facility**

### Main

Range of Product	Modicon X80
Product or Component Type	Switch module
Product Compatibility	BMEXBP... backplane

### Complementary

[Us] rated supply voltage	24 V back plane
Power consumption in W	3.3 W 135 mA 25 °C 4.5 W 185 mA 60 °C
Number of port	3
Integrated connection type	Ethernet/IP device network Ethernet/IP service port
Communication Port Protocol	EtherNet/IP
Local signalling	1 LED (green) for module active (RUN) 1 LED (red) for module error (ERR) 1 LED (green/red) for module status (Mod Status) 1 LED (green/red) for network communication status (Net Status)
Module format	Standard

### Environment

Marking	CE
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
IP Degree of Protection	IP20
Ambient Air Temperature for Operation	32...140 °F (0...60 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Operating altitude	<= 6561.68 ft (2000 m)
Maximum altitude transport	9842.5 ft (3000 m)
Overvoltage category	II
Relative Humidity	95 % without condensation

### Ordering and shipping details

Category	US1PC3418160
Discount Schedule	PC34
GTIN	3606480800061
Returnability	No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Country of origin	FR
-------------------	----

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Nbr. of units in pkg.	1
-----------------------	---

---

Package 1 Height	2.165 in (5.500 cm)
------------------	---------------------

---

Package 1 Width	4.331 in (11.000 cm)
-----------------	----------------------

---

Package 1 Length	4.528 in (11.500 cm)
------------------	----------------------

---

Package weight(Lbs)	9.065 oz (257.000 g)
---------------------	----------------------

---

Unit Type of Package 2	S02
------------------------	-----

---

Number of Units in Package 2	15
------------------------------	----

---

Package 2 Height	5.906 in (15.000 cm)
------------------	----------------------

---

Package 2 Width	11.811 in (30.000 cm)
-----------------	-----------------------

---

Package 2 Length	15.748 in (40.000 cm)
------------------	-----------------------

---

Package 2 Weight	9.121 lb(US) (4.137 kg)
------------------	-------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 165

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

Image of product / Alternate images

Alternative

---





