

# Product data sheet

Specifications



servo motor BMH, Lexium 32,  
48Nm, 4000rpm, keyed shaft,  
without brake, IP65, IP67, 128bit  
encoder

BMH1902P31A2A

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

Device short name	BMH
Product or Component Type	Servo motor
Maximum mechanical speed	4000 rpm
Continuous stall torque	331.02 lbf.in (37.4 N.m) LXM32.D72N4 24 A, 400 V, three phase 331.02 lbf.in (37.4 N.m) LXM32.D72N4 24 A, 480 V, three phase 424.8 lbf.in (48 N.m) LXM32MD85N4 32 A, 400 V, three phase 424.8 lbf.in (48 N.m) LXM32MD85N4 32 A, 480 V, three phase 424.8 lbf.in (48 N.m) LXM32MC10N4 40 A, 400 V, three phase 424.8 lbf.in (48 N.m) LXM32MC10N4 40 A, 480 V, three phase
Peak stall torque	893.9 lbf.in (101 N.m) LXM32.D72N4 24 A, 400 V, three phase 893.9 lbf.in (101 N.m) LXM32.D72N4 24 A, 480 V, three phase 1022.3 lbf.in (115.5 N.m) LXM32MD85N4 32 A, 400 V, three phase 1022.3 lbf.in (115.5 N.m) LXM32MD85N4 32 A, 480 V, three phase 1156.8 lbf.in (130.7 N.m) LXM32MC10N4 40 A, 400 V, three phase 1156.8 lbf.in (130.7 N.m) LXM32MC10N4 40 A, 480 V, three phase
Nominal output power	5900 W LXM32.D72N4 24 A, 400 V, three phase 5900 W LXM32.D72N4 24 A, 480 V, three phase 6070 W LXM32MD85N4 32 A, 400 V, three phase 6070 W LXM32MD85N4 32 A, 480 V, three phase 6070 W LXM32MC10N4 40 A, 400 V, three phase 6070 W LXM32MC10N4 40 A, 480 V, three phase
Nominal torque	197.4 lbf.in (22.3 N.m) LXM32.D72N4 24 A, 400 V, three phase 197.4 lbf.in (22.3 N.m) LXM32.D72N4 24 A, 480 V, three phase 256.7 lbf.in (29 N.m) LXM32MD85N4 32 A, 400 V, three phase 256.7 lbf.in (29 N.m) LXM32MD85N4 32 A, 480 V, three phase 256.7 lbf.in (29 N.m) LXM32MC10N4 40 A, 400 V, three phase 256.7 lbf.in (29 N.m) LXM32MC10N4 40 A, 480 V, three phase
Nominal speed	2000 rpm LXM32MC10N4 40 A, 400 V, three phase 2000 rpm LXM32MC10N4 40 A, 480 V, three phase 2500 rpm LXM32.D72N4 24 A, 400 V, three phase 2500 rpm LXM32.D72N4 24 A, 480 V, three phase 2000 rpm LXM32MD85N4 32 A, 400 V, three phase 2000 rpm LXM32MD85N4 32 A, 480 V, three phase
Product compatibility	LXM32.D72N4 400...480 V three phase
Shaft end	Keyed
IP Degree of Protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	131072 points/turn
Holding brake	Without
Mounting Support	International standard flange
Electrical Connection	Rotatable right-angled connectors

## Complementary

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Range Compatibility	Lexium 32
[Us] rated supply voltage	480 V
Phase	Three phase
Continuous stall current	30.8 A
Continuous power	6.1 W
Maximum current Irms	113.95 A LXM32.D72N4
Maximum permanent current	114 A
Second shaft	Without second shaft end
Shaft diameter	1.5 in (38 mm)
Shaft length	3.1 in (80 mm)
key width	2.8 in (70 mm)
Feedback type	Single turn SinCos Hiperface
Motor flange size	7.5 in (190 mm)
Number of motor stacks	2
Torque constant	1.56 N.m/A 248 °F (120 °C)
Back emf constant	108.3 V/krpm 248 °F (120 °C)
Number of motor poles	5.0
Rotor inertia	130.1 kg.cm <sup>2</sup>
Stator resistance	0.15 Ohm 68 °F (20 °C)
Stator inductance	1.93 mH 68 °F (20 °C)
Stator electrical time constant	25.7 ms 68 °F (20 °C)
Maximum radial force Fr	4200 N 1000 rpm
Maximum axial force Fa	0.2 x Fr
type of cooling	Natural convection
Length	9.8 in (250 mm)
Centring collar diameter	7.09 in (180 mm)
centring collar depth	0.2 in (4 mm)
Number of mounting holes	4
Mounting holes diameter	0.6 in (14 mm)
Circle diameter of the mounting holes	8.5 in (215 mm)
Net Weight	68.3 lb(US) (31 kg)
Sizing reference	BMH1902P
Network number of phases	3
Accuracy error [angular]	1.4 °
Temperature copper hot	275 °F (135 °C)
Temperature magnet hot	212 °F (100 °C)
Temperature magnet rt	68 °F (20 °C)

## Ordering and shipping details

Category	US1PC5318282
Discount Schedule	PC53

---

<b>GTIN</b>	3606485264158
<b>Returnability</b>	No
<b>Country of origin</b>	DE

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	11.81 in (30.0 cm)
<b>Package 1 Width</b>	15.75 in (40.0 cm)
<b>Package 1 Length</b>	31.30 in (79.5 cm)
<b>Package weight(Lbs)</b>	69.4 lb(US) (31.5 kg)

---

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **6675**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Pro-active compliance (Product out of EU RoHS legal scope)**

SCIP Number **A7df881f-135f-4256-b8c2-ea55d4c9a151**

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

PVC free **Yes**

## Use Again

### Repack and remanufacture

Circularity Profile **No need of specific recycling operations**

Take-back **No**

WEEE  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**