

Product data sheet

Specifications



Circuit breaker, ComPacT NSX630S DC, 100kA/750VDC, 3 poles, TM-DC trip unit 600A

C63S3TM600D

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	ComPacT
product name	ComPacT NSX DC
Device short name	NSX630S DC
Product or Component Type	Circuit breaker
Device Application	Distribution
Poles description	3P
Protected poles description	3D
Line Rated Current	600 A 104 °F (40 °C)
[Ue] rated operational voltage	750 V DC
Network type	DC
Suitability for isolation	Yes EN/IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	100 kA Icu 24...125 V DC 1 pole IEC 60947-2 100 kA Icu 250 V DC 1 pole IEC 60947-2 100 kA Icu 500 V DC 2 poles in series IEC 60947-2 100 kA Icu 750 V DC 3 poles in series IEC 60947-2
Performance level	S 100 kA 500 V DC
Trip unit name	TM-DC
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control Type	Toggle
Circuit breaker mounting mode	Fixed

Complementary

[Ui] rated insulation voltage	750 V DC IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kVIEC 60947-2
[Ics] rated service short-circuit breaking capacity	100 kA 24...125 V DC IEC 60947-2 100 kA 250 V DC IEC 60947-2 100 kA 500 V DC IEC 60947-2 100 kA 750 V DC IEC 60947-2
Mechanical durability	5000 cycles
Electrical durability	2000 cycles 750 V In/2 1000 cycles 750 V In
Mounting Support	Backplate

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Mounting position	Horizontal and vertical Flat on the back
Upside connection	Front
Downside connection	Front
Connection pitch	1.8 in (45 mm)
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	600 A 104 °F (40 °C)
Long-time pick-up adjustment type Ir (thermal protection)	Adjustable
[Ir] long-time protection pick-up adjustment range	0.7...1 x In
Long-time protection delay adjustment type tr	Fixed
Instantaneous protection pick-up adjustment type Ii	Adjustable
[Ii] instantaneous protection pick-up adjustment range	2.5...5 x In
Earth-leakage protection	Without
Number of slots for electrical auxiliaries	6
Width (W)	5.5 in (140 mm)
Height (H)	10.04 in (255 mm)
Depth (D)	4.3 in (110 mm)
Net Weight	17.6 lb(US) (8.0 kg)

Environment

Standards	EN/IEC 60947-2
Overtoltage category	Class II
Electrical shock protection class	Class II
Pollution degree	3 IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-58...185 °F (-50...85 °C)
Relative humidity	0...95 %
Operating altitude	0...6561.68 ft (0...2000 m) without derating 2000 m...5000 m with derating

Ordering and shipping details

Category	US10DE201101
Discount Schedule	0DE2
GTIN	3606481995087
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
Package 1 Height	5.91 in (15.000 cm)
Package 1 Width	6.10 in (15.500 cm)
Package 1 Length	11.61 in (29.500 cm)
Package 1 Weight	12.125 lb(US) (5.500 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	15.75 in (40.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	25.801 lb(US) (11.703 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	8
Package 3 Height	17.72 in (45.000 cm)
Package 3 Width	31.50 in (80.000 cm)
Package 3 Length	47.24 in (120.000 cm)
Package 3 Weight	129.658 lb(US) (58.812 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 2113

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Recycled metal content at CR level 0

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number E01033b9-a29d-4247-893c-b0642e7209e8

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Halogen content performance Product contains halogen above thresholds

PVC free Yes

Silicon free No

Use Again

Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Offer Marketing Illustration

Product benefits / Features

ComPacT NSX Moulded Case Circuit Breaker



Protection begins with prevention

Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



Maximize power availability

By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.



Offer Marketing Illustration

Product benefits / Features



ComPacT NSX
Range Accessories

Wireless auxiliary contact

Short terminal shield

Interphase barriers

Long terminal shield

Rotary handles

Standard auxiliary contact

MN undervoltage release

MX shunt release

Standard motor mechanism module

The image displays a collection of accessories for the ComPacT NSX circuit breaker range. It includes a main product image in the top left corner. Below it, nine individual accessories are shown in a 3x3 grid, each with a corresponding label: Wireless auxiliary contact, Short terminal shield, Interphase barriers, Long terminal shield, Rotary handles, Standard auxiliary contact, MN undervoltage release, MX shunt release, and Standard motor mechanism module.