Product data sheet

Specifications



Level 2 AC EV charger, Schneider Charge, Hardwired, 11.5kW/48A, NACS, with load management

EVRBA48ANAMJ3400

Product availability: Stock - Normally stocked in distribution facility

Main

Range	Schneider Charge
Product name	Schneider Charge
Product or Component Type	Car charger

Complementary

Connector Type	SAE J3400
Standards	UL 2594 UL 2231-1 UL 2231-2 UL 3141 ULC 3141 CSA C22.2 No 280-22 CSA C22.2 No 281.1-12 CSA C22.2 No 281.2-12
Product Certifications	UL ENERGY STAR (USA)
Ambient Air Temperature for Storage	-58…158 °F (-50…70 °C)
Relative humidity	0…95 %
Maximum supply current	48 A
Communication Network Type	Wi-Fi
Communication port protocol	OCPP 1.6
Ambient air temperature for operation	-22…122 °F (-30…50 °C)
IP degree of protection	Type 4 NEMA
Nominal output power	11500 W 48 A 208...240 V AC
Operating altitude	6561.68 ft (2000 m)
[Ue] rated operational voltage	208...240 V AC 60 Hz
Height	15.4 in (391.2 mm)
Width	6.83 in (173.48 mm)
Depth	4.06 in (103.12 mm)
Net Weight	12.8 lb(US) (5.8 kg)
Quantity per Set	1
Mounting Mode	Wall-mounted

Ordering and shipping details

Category	US1DE1021002

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Discount Schedule	DE10
GTIN	3606487391555
Returnability	Yes
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	11.8 in (30 cm)
Package 1 Width	11.02 in (28 cm)
Package 1 Length	18.7 in (47.5 cm)
Package weight(Lbs)	17.2 lb(US) (7.8 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**865 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**336 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**3 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**511 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**13 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and Nickel (Metallic), which are known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.**

Use Longer

Lifetime extension

Repair	**No**


Use Again

Repack and remanufacture

Recyclability potential, in %	**22**
Circularity Profile	End of Life Information
Removable battery	**No**

Image of product / Alternate images

Alternative


Dimensions
W 6.83 in
H 15.4 in
D 4.06 in
25 ft cable length
Schneider Charge


Schneider Charge


Schneider Charge
Charging
SESSION STATUS
Stop Charging




Level 2 charger with
NACS connector
Schneider Charge
Schneider

Image of product in real life situation

