

Product data sheet

Specifications



gearbox straight teeth GBX, Lexium,
60mm, reduction 5:1 , 10arc.min,
40N.m

GBX060005K

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Compatibility	Lexium 62 ILM Lexium ILS Lexium 32 Lexium 62 Lexium 28 Lexium ILA Lexium 52 Lexium SD3
Gear box type	Straight teeth
Product or Component Type	Planetary gearbox
Device short name	GBX
Product compatibility	BMH 2.8 in (70 mm), 1 BMH 2.8 in (70 mm), 2 BMH 2.8 in (70 mm), 3 BSH 2.2 in (55 mm), 1 BSH 2.2 in (55 mm), 2 BSH 2.2 in (55 mm), 3 BSH 2.8 in (70 mm), 1 BSH 2.8 in (70 mm), 2 BSH 2.8 in (70 mm), 3 BRS3 ILA 2.2 in (57 mm), 1 ILA 2.2 in (57 mm), 2 ILS 2.2 in (57 mm), 1 ILS 2.2 in (57 mm), 2 ILS 2.2 in (57 mm), 3 BCH2 2.4 in (60 mm), 1 BCH2 2.4 in (60 mm), 2 SH3 MH3 ILM
Gearbox external diameter	2.4 in (60 mm)
Reduction ratio	5:1

Complementary

Maximum torsional backlash	10 arc.min
Torsional rigidity	2.3 N.m/arcmin
Housing Colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Additional information	Lubricated for life
Service life in hours	30000 h 100 rpm 86 °F (30 °C)
Mounting position	Any position
Efficiency	96.0 %

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Maximum radial force Fr	340 N 100 rpm, force applied at mid-distance from output shaft during 30000 hour at 30 °C
Maximum axial force Fa	450 N 100 rpm, during 30000 hour at 30°C
moment of inertia	0.112 kg.cm ²
Continuous output torque	354.03 lbf.in (40 N.m) 100 rpm 86 °F (30 °C)
Maximum output torque	566.4 lbf.in (64 N.m) 100 rpm 86 °F (30 °C)
Net Weight	2.0 lb(US) (0.9 kg)
Input diameter	0.6 in (14.0 mm)
No load running torque	0.44 lbf.in (0.05 N.m)
Reduction ratio	5
Compatibility code	GBX
Internal length	1.5 in (39.0 mm)

Environment

Noise level	58 dB 1 m, no-load
IP Degree of Protection	Shaft output IP54
ambient temperature for operation	-13...194 °F (-25...90 °C)

Ordering and shipping details

Category	US1PC5318283
Discount Schedule	PC53
GTIN	3606480388200
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.677 in (6.800 cm)
Package 1 Width	2.677 in (6.800 cm)
Package 1 Length	5.118 in (13.000 cm)
Package weight(Lbs)	29.277 oz (830.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	19.074 lb(US) (8.652 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	7c9e597c-8ccc-4daf-95fb-5d67fc70d561
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes


Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No

Dimensions Drawings

Dimensions with Servo Motor Adaptation Kit



(1) GBK adaptation kit

(2) GBK adaptation kit related dimensions a1, c, Ø6, Ø7, Ø8 depend on the gearbox and servo motor combination

Ø8 shaft end adaptor in case motor shaft diameter is smaller than gearbox input coupling diameter

Values in mm

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5
55	35	30	2.5	16	5	60	40 h7	14 h7	M5 x 8	52

Values in in.

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5
2.16	1.38	1.18	0.10	0.63	0.19	2.36	1.57 h7	0.55 h7	M5 x 0.31	2.05