

Product data sheet

Specifications



gearbox straight teeth GBX, Lexium,
80mm, reduction 15:1 , 9arc.min,
110N.m

GBX080015K

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Compatibility	Lexium 32i Lexium 32 Lexium 62 Lexium 62 ILM Lexium 52 Lexium SD3 Lexium ILS Lexium 28
Gear box type	Straight teeth
Product or Component Type	Planetary gearbox
Device short name	GBX
Product compatibility	BMI 2.8 in (70 mm), 2 BMI 2.8 in (70 mm), 3 BMH 2.8 in (70 mm), 2 BMH 2.8 in (70 mm), 3 BSH 2.8 in (70 mm), 2 BSH 2.8 in (70 mm), 3 BMH 3.9 in (100 mm), 1 BSH 3.9 in (100 mm), 1 BRS3 ILS 3.3 in (85 mm), 1 ILS 3.3 in (85 mm), 2 ILS 3.3 in (85 mm), 3 BCH2 3.1 in (80 mm), 1 BCH2 3.1 in (80 mm), 2 SH3 MH3 ILM
Gearbox external diameter	3.1 in (80 mm)
Reduction ratio	15:1

Complementary

Maximum torsional backlash	9 arc.min
Torsional rigidity	6.5 N.m/arcmin
Housing Colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Additional information	Lubricated for life
Service life in hours	30000 h 100 rpm 86 °F (30 °C)
Mounting position	Any position
Efficiency	96.0 %
Maximum radial force Fr	650 N 100 rpm, force applied at mid-distance from output shaft during 30000 hour at 30 °C

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Maximum axial force Fa	1200 N 100 rpm, during 30000 hour at 30°C
moment of inertia	0.423 kg.cm ²
Continuous output torque	973.6 lbf.in (110 N.m) 100 rpm 86 °F (30 °C)
Maximum output torque	1557.7 lbf.in (176 N.m) 100 rpm 86 °F (30 °C)
Net Weight	5.7 lb(US) (2.6 kg)
Input diameter	0.7 in (19.0 mm)
No load running torque	0.9 lbf.in (0.1 N.m)
Reduction ratio	15
Compatibility code	GBX
Internal length	3.5 in (89.5 mm)

Environment

Noise level	60 dB 1 m, no-load
IP Degree of Protection	Shaft output IP54
ambient temperature for operation	-13...194 °F (-25...90 °C)

Ordering and shipping details

Category	US1PC5318283
Discount Schedule	PC53
GTIN	3606480388378
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.2 in (10.6 cm)
Package 1 Width	4.2 in (10.6 cm)
Package 1 Length	7.09 in (18.0 cm)
Package weight(Lbs)	5.322 lb(US) (2.414 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	22.381 lb(US) (10.152 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 1170

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number 7c9e597c-8ccc-4daf-95fb-5d67fc70d561

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

PVC free Yes

Use Again


Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No

Dimensions Drawings

Dimensions with Servo Motor Adaptation Kit



- (1) GBK adaptation kit
- (2) GBK adaptation kit related dimensions a1, c, Ø6, Ø7, Ø8 depend on the gearbox and servo motor combination
- Ø8 shaft end adaptor in case motor shaft diameter is smaller than gearbox input coupling diameter

Values in mm

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5
89.5	40	36	4	22.5	6	80	60 h7	20 h7	M6 x 10	70

Values in in.

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5
3.52	1.57	1.42	0.16	089	0.24	3.15	2.36 h7	0.79 h7	M6 x 0.39	2.76