



## Main

Range Compatibility	Lexium 32 Lexium 62 Lexium 28 Lexium 62 ILM Lexium 52
Gear box type	Straight teeth
Product or Component Type	Planetary gearbox
Device short name	GBX
Product compatibility	BMH 3.9 in (100 mm), 3 BSH 3.9 in (100 mm), 1 BSH 3.9 in (100 mm), 3 BCH2 3.9 in (100 mm), 1 BCH2 5.1 in (130 mm), 1 SH3 MH3 ILM
Gearbox external diameter	4.7 in (120 mm)
Reduction ratio	10:1

## Complementary

Maximum torsional backlash	7 arc.min
Torsional rigidity	12 N.m/arcmin
Housing Colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Additional information	Lubricated for life
Service life in hours	30000 h 100 rpm 86 °F (30 °C)
Mounting position	Any position
Efficiency	96 %
Maximum radial force Fr	1500 N 100 rpm, force applied at mid-distance from output shaft during 30000 hour at 30 °C
Maximum axial force Fa	2100 N 100 rpm, during 30000 hour at 30°C
Moment of inertia	1.3 kg.cm <sup>2</sup>
Continuous output torque	840.8 lbf.in (95 N.m) 100 rpm 86 °F (30 °C)
Maximum output torque	1345.3 lbf.in (152 N.m) 100 rpm 86 °F (30 °C)
Net Weight	13.2 lb(US) (6 kg)
Input diameter	0.9 in (24.0 mm)

## Environment

Noise level	65 dB 1 m, no-load
IP Degree of Protection	Shaft output IP54
Ambient temperature for operation	-13...194 °F (-25...90 °C)

## Ordering and shipping details

Category	US1PC5318283
Discount Schedule	PC53
GTIN	3606485317502
Returnability	No
Country of origin	DE


## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 in (19.0 cm)
Package 1 Width	5.1 in (13.0 cm)
Package 1 Length	5.1 in (13.0 cm)
Package 1 Weight	12.090 lb(US) (5.484 kg)
Unit Type of Package 2	S02
Number of Units in Package 2	2
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	25.183 lb(US) (11.423 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
PVC free	Yes

Dimensions with Servo Motor Adaptation Kit



(1) GBK adaptation kit

(2) GBK adaptation kit related dimensions a1, c, Ø6, Ø7, Ø8 depend on the gearbox and servo motor combination  
Ø8 shaft end adaptor in case motor shaft diameter is smaller than gearbox input coupling diameter

Values in mm

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5
99.5	55	50	5	28	8	115	80 h7	25 h7	M10 x 16	100

Values in in.

a2	a3	a4	a5	h	g	Ø1	Ø2	Ø3	Ø4	Ø5
3.92	2.17	1.97	0.19	1.10	0.31	4.53	3.15 h7	0.98 h7	M10 x 0.63	3.94