



Main

| | |
|---------------------------|---|
| Range | Easy TeSys |
| Device short name | GPEFC |
| Product or Component Type | Auxiliary contact block |
| Mounting Location | Front side |
| Pole contact composition | 1 NO + 1 NC |
| Connections - terminals | Screw clamp terminals1 0.00...0.00 in ² (1... 2.5 mm ²) - solid Screw clamp terminals2 0.00...0.00 in ² (1... 2.5 mm ²) - solid Screw clamp terminals1 0.00...0.00 in ² (0.75... 2.5 mm ²) - flexible without cable end Screw clamp terminals2 0.00...0.00 in ² (0.75... 2.5 mm ²) - flexible without cable end Screw clamp terminals1 0.00...0.00 in ² (0.75... 1.5 mm ²) - flexible with cable end |
| Quantity per Set | Set of 10 |

Complementary

| | |
|---|--|
| [Ui] rated insulation voltage | 300 V UL 60947-4-1 300 V cUL 250 V IEC 60947-1 |
| [Ue] rated operational voltage | 24...240 V AC 24...60 V DC |
| [Ith] conventional free air thermal current | 2.5 A |
| Mechanical durability | 100000 cycles |
| Minimum switching current | 5 mA |
| Minimum switching voltage | 17 V |
| Protection type | GG fuse 10 A GB2CB06 circuit breaker 10 A |
| Rated operational power in VA | 120 VA 110...120 V AC-15 100000 cycles 120 VA 230...240 V AC-15 100000 cycles 48 VA 24 V AC-15 100000 cycles 60 VA 48 V AC-15 100000 cycles |
| Rated operational power in W | 15 W 48 V DC-13 100000 cycles 24 W 24 V DC-13 100000 cycles 9 W 60 V DC-13 100000 cycles |
| Tightening torque | 12.39 lbf.in (1.4 N.m) screw clamp terminals |
| Height | 0.43 in (11 mm) |
| Width | 1.77 in (45 mm) |
| Depth | 1.14 in (29 mm) |
| Net Weight | 0.04 lb(US) (0.02 kg) |

Environment

| | |
|------------------------------|--------------------|
| Environmental characteristic | Normal environment |
|------------------------------|--------------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10I1322364 |
| Discount Schedule | 0I13 |
| GTIN | 3606481063496 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 0.50 in (1.27 cm) |
| Package 1 Width | 1.30 in (3.3 cm) |
| Package 1 Length | 1.80 in (4.57 cm) |
| Package 1 Weight | 0.04 lb(US) (0.02 kg) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 220 |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 Width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |
| Package 2 Weight | 10.75 lb(US) (4.877 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |