

Product data sheet

Specifications



Current limiter, TeSys Deca Frame
2,32A/690V, activation 1.5kA, at top
of GV2ME/GV2P/GV2RT with screw
clamp connections

GV1L3

Product availability: Stock - Normally stocked in distribution
facility

Main

Range	TeSys
Range of Product	TeSys GV2 TeSys Deca
Accessory / separate part category	Protection accessory
Product or Component Type	Current limiting module
Range compatibility	TeSys GV2 TeSys Deca
Product Compatibility	GV2RT GV2ME GV2P GV2L
Function of module	Increasing the breaking capacity of a circuit breaker
Mounting Location	On top of the circuit breaker
[Ie] rated operational current	32 A
[Ith] conventional free air thermal current	63 A IEC 60947-1
Activation threshold	1500 A
Breaking capacity	<= 100 kA depending on protective device
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Ui] rated insulation voltage	690 V AC 50/60 Hz IEC 60947-1

Complementary

Connections - terminals	Screw clamp terminals 1 x 0.002...0.04 in ² (1.5...25 mm ²) rigid Screw clamp terminals 2 x 0.002...0.02 in ² (1.5...10 mm ²) rigid Screw clamp terminals 1 x 0.002...0.04 in ² (1.5...25 mm ²) flexible without cable end Screw clamp terminals 2 x 0.002...0.02 in ² (1.5...10 mm ²) flexible without cable end Screw clamp terminals 1 x 0.002...0.02 in ² (1.5...16 mm ²) flexible with cable end Screw clamp terminals 2 x 0.002...0.006 in ² (1.5...4 mm ²) flexible with cable end
Tightening torque	19.5 lbf.in (2.2 N.m)
Net Weight	0.29 lb(US) (0.13 kg)

Ordering and shipping details

Category	US10I122366
Discount Schedule	0I11
GTIN	3389110209952
Returnability	Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin	FR
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	3.35 in (8.5 cm)
------------------	------------------

Package 1 Width	1.97 in (5.0 cm)
-----------------	------------------

Package 1 Length	3.15 in (8.0 cm)
------------------	------------------

Package weight(Lbs)	4.3 oz (122.0 g)
---------------------	------------------

Unit Type of Package 2	S01
------------------------	-----

Number of Units in Package 2	24
------------------------------	----

Package 2 Height	5.91 in (15.0 cm)
------------------	-------------------

Package 2 Width	5.91 in (15.0 cm)
-----------------	-------------------

Package 2 Length	15.75 in (40.0 cm)
------------------	--------------------

Package 2 Weight	6.843 lb(US) (3.104 kg)
------------------	-------------------------

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	42
--	----

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	Yes
--------------------------------------	-----

EU RoHS Directive	Compliant
-----------------------------------	-----------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
---------------------------	--

Use Again

Repack and remanufacture

Take-back	No
-----------	----

Connections and Schema

Current Limiter

GV1L3

