

# Product data sheet

Specifications



## Auxiliary contact block, TeSys GV4, 2NO+2NC, SDx contact module for GV4PEM

GV4ADM1111

### Main

Range	TeSys
Device short name	GV4A
Product or component type	Auxiliary contact block
Product compatibility	GV4
Mounting location	Right side
Auxiliary contacts operation	Signalling
Pole contact composition	2 NO + 2 NC

### Complementary

[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
[Ue] rated operational voltage	24...250 V AC 24...250 V DC
[Ith] conventional free air thermal current	5 A
Mechanical durability	100000 cycles
Minimum switching current	2 mA
Minimum switching voltage	17 V
Protection type	GG fuse 5 A
Rated operational power in VA	400 VA at 230...240 V AC-12
Rated operational power in W	50 W at 24 V DC-12

### Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	9 cm
Package 1 Length	15.6 cm
Package 1 Weight	150 g
Unit Type of Package 2	S02
Number of Units in Package 2	18

Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
SCIP Number	50a98d63-e355-4cae-a24f-48edbc8c4dc5

## Use Again

### Repack and remanufacture

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins