

# Product data sheet

Specifications



## TeSys Deca - auxiliary contact - 1 NO + 1 NO (fault)

GVAD1010

**Product availability: Stock - Normally stocked in distribution facility**

### Main

<b>Range</b>	TeSys TeSys Deca
<b>Device short name</b>	GVAD
<b>Product or Component Type</b>	Auxiliary contact block
<b>Product Compatibility</b>	GV2L GV2P GV2RT GV3L GV2LE GV3P GV2ME
<b>Mounting Location</b>	Left side
<b>Auxiliary contacts operation</b>	Fault signal 1 NO
<b>Pole contact composition</b>	2 NO

### Complementary

<b>[Ui] rated insulation voltage</b>	690 V IEC 60947-1 300 V UL 508 300 V CSA C22.2 No 14
<b>[Ue] rated operational voltage</b>	48...690 V AC 24...240 V DC
<b>[Ith] conventional free air thermal current</b>	6 A 2.5 A for fault signalling
<b>Mechanical durability</b>	100000 cycles
<b>Minimum switching current</b>	5 mA
<b>Minimum switching voltage</b>	17 V
<b>Protection type</b>	GB2CB... circuit breaker GG fuse 10 A
<b>Rated operational power in VA</b>	300 VA 48 V AC-15 100000 cycles 414 VA 690 V AC-15 100000 cycles 500 VA 110...127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230...240 V AC-15 100000 cycles 850 VA 380...415 V AC-15 100000 cycles 36 VA 24 V AC-14 1000 cycles 48 VA 48 V AC-14 1000 cycles 72 VA 110...127 V AC-14 1000 cycles

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Rated operational power in W</b>	120 W 240 V DC-13 100000 cycles 140 W 110 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 180 W 60 V DC-13 100000 cycles 240 W 48 V DC-13 100000 cycles 15 W 48 V DC-13 1000 cycles 24 W 24 V DC-13 1000 cycles 9 W 60 V DC-13 1000 cycles
<b>Tightening torque</b>	12.4 lbf.in (1.4 N.m) screw clamp terminals
<b>Height</b>	3.5 in (89 mm)
<b>Width</b>	0.4 in (9.3 mm)
<b>Depth</b>	2.6 in (66 mm)
<b>Net Weight</b>	0.121 lb(US) (0.055 kg)
<b>color</b>	Dark grey

## Environment

<b>Environmental characteristic</b>	Normal environment
<b>Product Certifications</b>	UKCA

## Ordering and shipping details

<b>Category</b>	US10I1122367
<b>Discount Schedule</b>	0111
<b>GTIN</b>	3389110343557
<b>Returnability</b>	Yes
<b>Country of origin</b>	CZ

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	0.591 in (1.500 cm)
<b>Package 1 Width</b>	2.559 in (6.500 cm)
<b>Package 1 Length</b>	3.425 in (8.700 cm)
<b>Package weight(Lbs)</b>	1.481 oz (42.000 g)
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	3.740 in (9.500 cm)
<b>Package 2 Width</b>	3.937 in (10.000 cm)
<b>Package 2 Length</b>	5.906 in (15.000 cm)
<b>Package 2 Weight</b>	16.578 oz (470.000 g)
<b>Unit Type of Package 3</b>	S02
<b>Number of Units in Package 3</b>	60
<b>Package 3 Height</b>	5.906 in (15.000 cm)
<b>Package 3 Width</b>	11.811 in (30.000 cm)
<b>Package 3 Length</b>	15.748 in (40.000 cm)
<b>Package 3 Weight</b>	6.834 lb(US) (3.100 kg)

# Contractual warranty

---

Warranty

18 months



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	1
--	---

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	Yes
--------------------------------------	-----

<a href="#">EU RoHS Directive</a>	Compliant
-----------------------------------	-----------

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
---------------------------	--

## Use Again

### Repack and remanufacture

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---


Take-back	No
-----------	----

WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
------------	--

Connections and Schema

---

GVAD1010



Technical Illustration

Assembly's dimensions

---

