

Product data sheet

Specifications



TeSys Deca - auxiliary contact block - 2 NO

GVAED101

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys TeSys Deca
Device short name	GVAED
Product or Component Type	Auxiliary contact block
Product Compatibility	GV3P GV3L
Mounting Location	Front side
Auxiliary contacts operation	Fault signal 1 NO
Pole contact composition	2 NO
Quantity per Set	Set of 1

Complementary

[Ui] rated insulation voltage	600 V UL 508 690 V IEC 60947-1 600 V CSA C22.2 No 14
[Ue] rated operational voltage	24...240 V AC 24...60 V DC
[Ith] conventional free air thermal current	2.5 A
Mechanical durability	100000 cycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Protection type	GB2CB... circuit breaker GG fuse 10 A
Rated operational power in VA	300 VA 48 V AC-15 100000 cycles 400 VA 690 V AC-15 100000 cycles 500 VA 110...127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230...240 V AC-15 100000 cycles 850 VA 380...415 V AC-15 100000 cycles
Rated operational power in W	120 W 240 V DC-13 100000 cycles 140 W 110 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 180 W 60 V DC-13 100000 cycles 240 W 48 V DC-13 100000 cycles
Tightening torque	12.4 lbf.in (1.4 N.m) screw clamp terminals
Height	0.4 in (11 mm)
Width	1.8 in (45 mm)
Depth	1.1 in (29 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net Weight	0.11 lb(US) (0.05 kg)
------------	-----------------------

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Product Certifications	UKCA
------------------------	------

Ordering and shipping details

Category	US10I1122367
----------	--------------

Discount Schedule	0I11
-------------------	------

GTIN	3389119405478
------	---------------

Returnability	No
---------------	----

Country of origin	CZ
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	0.5 in (1.2 cm)
------------------	-----------------

Package 1 Width	2.0 in (5.0 cm)
-----------------	-----------------

Package 1 Length	2.4 in (6.0 cm)
------------------	-----------------

Package weight(Lbs)	0.6 oz (18.0 g)
---------------------	-----------------

Unit Type of Package 2	BB1
------------------------	-----

Number of Units in Package 2	10
------------------------------	----

Package 2 Height	1.2 in (3.0 cm)
------------------	-----------------

Package 2 Width	5.9 in (15.0 cm)
-----------------	------------------

Package 2 Length	6.3 in (16.0 cm)
------------------	------------------

Package 2 Weight	6.6 oz (186.0 g)
------------------	------------------

Unit Type of Package 3	S02
------------------------	-----

Number of Units in Package 3	220
------------------------------	-----

Package 3 Height	5.9 in (15.0 cm)
------------------	------------------

Package 3 Width	11.8 in (30.0 cm)
-----------------	-------------------

Package 3 Length	15.7 in (40.0 cm)
------------------	-------------------

Package 3 Weight	9.689 lb(US) (4.395 kg)
------------------	-------------------------

Contractual warranty

Warranty	18 months
----------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	1
--	---

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	Yes
--------------------------------------	-----

EU RoHS Directive	Compliant
-----------------------------------	-----------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
---------------------------	--

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
---------------------	---

Take-back	No
-----------	----

WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
------------	--

Connections and Schema

GVAED101




Image of product / Alternate images

Alternative



