

Product data sheet

Specifications



Circuit breaker, PowerPacT J, 250A, 3 pole, 600VAC, 50kA, I-Line, Micrologic 3.2, 80%, ABC

JLA36250U31X

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type Circuit breaker

Complementary

| | |
|---|---|
| Line Rated Current | 250 A |
| Number of Poles | 3P |
| Control Type | Toggle |
| Breaking capacity code | L |
| Breaking capacity | 125 kA 240 V AC 50/60 Hz UL 489 100 kA 480 V AC 50/60 Hz UL 489 50 kA 600 V AC 50/60 Hz UL 489 20 kA 250 V DC UL 489 50 kA 500 V DC UL 489 |
| [Ue] rated operational voltage | 600 V AC 50/60 Hz IEC 60947-3 |
| Network Frequency | 50/60 Hz |
| [Ics] rated service breaking capacity | 125 kA 220/240 V AC 50/60 Hz IEC 60947-2 100 kA 380/440/415 V AC 50/60 Hz IEC 60947-2 50 kA 500/525 V AC 50/60 Hz IEC 60947-2 20 kA 250 V DC IEC 60947-2 20 kA 500 V DC IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 8 kV IEC 60947-2 |
| Trip unit technology | Electronic, standard, MicroLogic 3.2, LI |
| Continuous current rating | 80 % |
| [Ui] rated insulation voltage | 750 V IEC 60947-2 |
| Trip unit name | MicroLogic 3.2 |
| Protection Type | Overload protection Short-circuit protection |
| Suitability for isolation | Yes IEC 60947-2 |
| Utilisation category | Category A |
| AWG gauge | AWG 3/0...350 kcmil aluminium/copper terminals |
| Local signalling | Ready 1 LED green) Alarm 1 LED 90 % Ir orange) Alarm 1 LED 105 % Ir red) Switched off (OFF) 1 trip indicator green) |
| Mounting mode | I-Line bracket) |
| Mounting Support | Bracket |
| Electrical connection | I-Line connection, line Lugs, load |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|------------------------------------|---|
| Terminal identifier | AL250JD |
| Long time pick-up adjustment range | 0.25...1 x In |
| Mounting Height | 4.5 in (114.3 mm) |
| Tightening torque | 221.3 lbf.in (25 N.m) 0.1...0.3 in ² (95...185 mm ²) (AWG 3/0...350 kcmil) |
| Number of slots | 2 auxiliary switch OF plug-in) 1 alarm switch SD plug-in) 1 overcurrent trip switch SDE plug-in) 1 voltage release MN or MX plug-in) |
| Power wire stripping length | 1.0 in (25 mm) |
| Height | 7.5 in (191 mm) |
| Width | 4.09 in (104 mm) |
| Depth | 3.4 in (86 mm) |
| Net Weight | 5.3 lb(US) (2.4 kg) |
| Phase connection | ABC |
| Communication interface | Modbus |
| Circuit breaker application | HACR rated |

Environment

| | |
|---------------------------------------|--|
| Quality labels | CE |
| Standards | UL CSA NEMA NOM-003-SCFI-2000 IEC 60947-2 |
| Product certifications | UL CSA NOM |
| IP degree of protection | Front cover IP40 |
| Pollution degree | 3 |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -58...185 °F (-50...85 °C) |
| Operating altitude | < 6561.68 ft (2000 m) without derating 5000 m with derating |

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10DE201104 |
| Discount Schedule | 0DE2 |
| GTIN | 3606486283455 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 5.38 in (13.653 cm) |
| Package 1 Width | 8.13 in (20.638 cm) |

| | |
|----------------------------|-------------------------|
| Package 1 Length | 14.63 in (37.148 cm) |
| Package weight(Lbs) | 6.074 lb(US) (2.755 kg) |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 559

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

California proposition 65 **WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

PVC free Yes

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery No

Take-back No

Technical Illustration

Dimensions

