

# Product data sheet

Specifications



## Auxiliary contact block, TeSys Deca, 1NO(sealed)+1NC(sealed), front, screw clamp terminals

LA1DX11

**Product availability: Non-Stock - Not normally stocked in distribution facility**

### Main

Range	TeSys
Product name	TeSys Deca
Product or Component Type	Auxiliary contact block
Device short name	LA1
Range compatibility	TeSys D CAD TeSys D LC1D TeSys F LC1F TeSys F CR1F TeSys Deca CAD TeSys Deca LC1D
Mounting Location	Front
Pole contact composition	1 NO (sealed) + 1 NC (sealed)
Contacts operation	Instantaneous
[Ue] rated operational voltage	125 V AC protected contact 30 V DC protected contact
[Ie] rated operational current	0.1 A
[Ui] rated insulation voltage	250 V IEC 60947-5-1
Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5
Product Certifications	CB UL CSA CCC EAC UKCA

### Complementary

Mechanical durability	5 Mcycles
Minimum switching current	1 mA
Minimum switching voltage	5 V
Insulation resistance	> 10 MOhm
Connections - terminals	screw clamp terminals 1 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible with cable end screw clamp terminals 1 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible without cable end screw clamp terminals 2 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible with cable end screw clamp terminals 2 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible without cable end screw clamp terminals 1 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )rigid screw clamp terminals 2 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )rigid

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Tightening torque</b>	15.05 lbf.in (1.7 N.m) flat Ø 6 mm 15.05 lbf.in (1.7 N.m) Philips No 2 15.05 lbf.in (1.7 N.m) pozidriv No 2
<b>Height</b>	1.9 in (48 mm)
<b>Width</b>	1.7 in (44 mm)
<b>Depth</b>	1.5 in (39 mm)
<b>Net Weight</b>	0.09 lb(US) (0.04 kg)

## Environment

<b>Environmental characteristic</b>	Harsh environment
<b>IP degree of protection</b>	IP2X conforming to IEC 60529
<b>Protective treatment</b>	TH IEC 60068
<b>Ambient Air Temperature for Storage</b>	-13...158 °F (-25...70 °C)
<b>Ambient Air Temperature for Operation</b>	-13...158 °F (-25...70 °C)

## Ordering and shipping details

<b>Category</b>	US10I1222341
<b>Discount Schedule</b>	0112
<b>GTIN</b>	3389110970609
<b>Returnability</b>	No
<b>Country of origin</b>	CZ

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	1.6 in (4.0 cm)
<b>Package 1 Width</b>	1.9 in (4.8 cm)
<b>Package 1 Length</b>	2.05 in (5.2 cm)
<b>Package weight(Lbs)</b>	1.8 oz (52.0 g)
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	2.0 in (5.0 cm)
<b>Package 2 Width</b>	3.3 in (8.5 cm)
<b>Package 2 Length</b>	10.2 in (26.0 cm)
<b>Package 2 Weight</b>	18.3 oz (520.0 g)
<b>Unit Type of Package 3</b>	S02
<b>Number of Units in Package 3</b>	80
<b>Package 3 Height</b>	5.9 in (15.0 cm)
<b>Package 3 Width</b>	11.8 in (30.0 cm)
<b>Package 3 Length</b>	15.7 in (40.0 cm)
<b>Package 3 Weight</b>	9.958 lb(US) (4.517 kg)



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	2
--	---

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	Yes
--------------------------------------	-----

<a href="#">EU RoHS Directive</a>	Compliant
-----------------------------------	-----------

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

## Use Again

### Repack and remanufacture

Take-back	No
-----------	----

WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
------------	--