

Product data sheet

Specifications



Auxiliary contact block, TeSys Deca, 2NO(sealed), front mounting

LA1DY20

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Product name	TeSys Deca
Product or Component Type	Auxiliary contact block
Device short name	LA1
Range compatibility	TeSys D CAD TeSys D LC1D TeSys F LC1F TeSys F CR1F TeSys Deca CAD TeSys Deca LC1D
Mounting Location	Front
Pole contact composition	2 earth screen continuity poles 2 NO (sealed)
Contacts operation	Instantaneous
[Ue] rated operational voltage	125 V AC protected contact 30 V DC protected contact
[Ie] rated operational current	0.1 A
[Ui] rated insulation voltage	250 V IEC 60947-5-1
Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5
Product Certifications	CB UL CSA CCC EAC UKCA

Complementary

Mechanical durability	5 Mcycles
Minimum switching current	1 mA
Minimum switching voltage	5 V
Insulation resistance	> 10 MOhm
Connections - terminals	screw clamp terminals 1 0.002...0.004 in ² (1...2.5 mm ²)flexible with cable end screw clamp terminals 1 0.002...0.004 in ² (1...2.5 mm ²)flexible without cable end screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²)flexible with cable end screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²)flexible without cable end screw clamp terminals 1 0.002...0.004 in ² (1...2.5 mm ²)rigid screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²)rigid

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Tightening torque	15.05 lbf.in (1.7 N.m) flat Ø 6 mm 15.05 lbf.in (1.7 N.m) Philips No 2 15.05 lbf.in (1.7 N.m) pozidriv No 2
Height	1.9 in (48 mm)
Width	1.7 in (44 mm)
Depth	1.5 in (39 mm)
Net Weight	0.09 lb(US) (0.04 kg)
Quantity per Set	Set of 2

Environment

Environmental characteristic	Harsh environment
IP degree of protection	IP2X conforming to IEC 60529
Protective treatment	TH IEC 60068
Ambient Air Temperature for Storage	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)

Ordering and shipping details

Category	US101222341
Discount Schedule	0112
GTIN	3389110236514
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.850 in (4.700 cm)
Package 1 Width	1.890 in (4.800 cm)
Package 1 Length	2.087 in (5.300 cm)
Package weight(Lbs)	2.257 oz (64.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	80
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	12.050 lb(US) (5.466 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	4
--	---

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	Yes
--------------------------------------	-----

EU RoHS Directive	Compliant
-----------------------------------	-----------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

Use Again

Repack and remanufacture

Take-back	No
-----------	----

WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
------------	--