

# Product data sheet

Specifications



Electronic time delay auxiliary contact block, TeSys K, 1C/O, on delay 1-30s, front, control 110...240V AC

LA2KT2U

## Main

Range	TeSys
Product name	TeSys K
Product or component type	Time delay auxiliary contact block
Device short name	LA1
Range compatibility	TeSys K LC1K TeSys K CA2K TeSys K CA3K TeSys K CA4K
Mounting location	Front
Pole contact composition	1 C/O
Contacts operation	Time delay
Timer type	On delay
Time delay range	1...30 s
[Ue] rated operational voltage	110...240 V AC for control circuit 240 V AC for signalling circuit
Rated operational voltage limits	0.85...1.1 U <sub>c</sub>
[I <sub>th</sub> ] conventional free air thermal current	2 A for signalling circuit
Standards	EN/IEC 60947-5-1
Product certifications	CE UKCA

## Complementary

Insulation resistance	> 10 MΩ
Connections - terminals	Slip-on terminals
Reset time	1.5 s during time delay 0.5 s after time delay
Height	27 mm
Width	38 mm
Depth	38 mm
Net weight	0.04 kg

## Environment

Environmental characteristic	Normal environment
IP degree of protection	IP20 conforming to IEC 60529

---

<b>Protective treatment</b>	TC conforming to IEC 60068
-----------------------------	----------------------------

---

<b>Ambient air temperature for operation</b>	-10...60 °C
--	-------------

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	5.000 cm
-------------------------	----------

---

<b>Package 1 Width</b>	4.800 cm
------------------------	----------

---

<b>Package 1 Length</b>	4.800 cm
-------------------------	----------

---

<b>Package 1 Weight</b>	44.000 g
-------------------------	----------

---

<b>Unit Type of Package 2</b>	S02
-------------------------------	-----

---

<b>Number of Units in Package 2</b>	70
-------------------------------------	----

---

<b>Package 2 Height</b>	15.000 cm
-------------------------	-----------

---

<b>Package 2 Width</b>	30.000 cm
------------------------	-----------

---

<b>Package 2 Length</b>	40.000 cm
-------------------------	-----------

---

<b>Package 2 Weight</b>	3.361 kg
-------------------------	----------

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint	4
----------------------------------	---

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	Yes
--------------------------------------	-----

<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
-----------------------------------	---------------------------

SCIP Number	8a21c0d1-be95-4e83-b703-1e8075e942f8
-------------	--------------------------------------

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

## Use Again

### Repack and remanufacture

End of life manual availability	No need of specific recycling operations
---------------------------------	--

Take-back	No
-----------	----

WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------------	---

Technical Illustration

Assembly's dimensions

---

