

# Product data sheet

Specifications



## Auxiliary contact block, TeSys Deca, 4NC, front mounting, spring terminals

LADN043

### Main

<b>Range</b>	TeSys TeSys Deca
<b>Product name</b>	TeSys Deca
<b>Product or component type</b>	Auxiliary contact block
<b>Device short name</b>	LADN
<b>Range compatibility</b>	TeSys Deca CAD TeSys Deca LC1D
<b>Mounting location</b>	Front
<b>Pole contact composition</b>	4 NC
<b>Contacts operation</b>	Instantaneous
<b>[Ue] rated operational voltage</b>	690 V AC 25...400 Hz
<b>[Ie] rated operational current</b>	6 A at 120 V AC-15 1.04 A at 690 V AC-15 0.55 A at 125 V DC-13 0.1 A at 600 V DC-13
<b>[Ui] rated insulation voltage</b>	690 V conforming to IEC 60947-5-1 600 V conforming to UL 60947-5-1 600 V conforming to CSA C22.2 No 60947-5-1
<b>[Ith] conventional free air thermal current</b>	10 A (at 60 °C)
<b>Standards</b>	EN/IEC 60947-5-1 GB/T 14048.5 EN 50012 UL 60947-5-1 CSA C22.2 No 60947-5-1 IEC 60335-1:Clause 30.2 IEC 60335-2-40:Annex JJ UL 60335-2-40:Annex JJ
<b>Product certifications</b>	CB Scheme UL CSA CCC EAC UKCA

### Complementary

<b>Irms rated making capacity</b>	140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1
<b>Permissible short-time rating</b>	100 A 60 °C 1 s 120 A 60 °C 500 ms 140 A 60 °C 100 ms
<b>Protection type</b>	GG fuse 10 A
<b>Mechanical durability</b>	30 Mcycles

<b>Minimum switching current</b>	5 mA
<b>Minimum switching voltage</b>	17 V
<b>Non-overlap time</b>	1.5 ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact
<b>Insulation resistance</b>	> 10 MOhm
<b>Connections - terminals</b>	Spring terminals 2 cable(s) 2.5 mm <sup>2</sup> flexible without cable end Spring terminals 2 cable(s) 2.5 mm <sup>2</sup> rigid
<b>Height</b>	48 mm
<b>Width</b>	44 mm
<b>Depth</b>	42 mm
<b>Net weight</b>	0.05 kg
<b>Colour</b>	Dark grey

## Environment

<b>Environmental characteristic</b>	Normal environment
<b>IP degree of protection</b>	IP20 conforming to IEC 60529
<b>Protective treatment</b>	TH conforming to IEC 60068
<b>Ambient air temperature for storage</b>	-60...80 °C
<b>Ambient air temperature for operation</b>	-5...60 °C
<b>Operating altitude</b>	3000 m

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.2 cm
<b>Package 1 Width</b>	4.8 cm
<b>Package 1 Length</b>	4.1 cm
<b>Package 1 Weight</b>	67.0 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	5.2 cm
<b>Package 2 Width</b>	8.5 cm
<b>Package 2 Length</b>	25.5 cm
<b>Package 2 Weight</b>	673.0 g
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	160
<b>Package 3 Height</b>	30.0 cm
<b>Package 3 Width</b>	30.0 cm
<b>Package 3 Length</b>	40.0 cm
<b>Package 3 Weight</b>	11.23 kg



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint	7
----------------------------------	---

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	Yes
--------------------------------------	-----

<a href="#">EU RoHS Directive</a>	Compliant
-----------------------------------	-----------

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

## Use Again

### Repack and remanufacture

End of life manual availability	No need of specific recycling operations
---------------------------------	--

Take-back	No
-----------	----

WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------------	---