

Product data sheet

Specifications



Disconnect Switch, TeSys LK, nonfusible, 200A, 600 V, HP rated, 3 pole, rotary handle, up to 200kA SCCR

LK4MU3N

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Product name	TeSys LK
Product or Component Type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes

Complementary

Poles description	3P
Network type	AC DC
Network Frequency	50/60 Hz
[Ie] rated operational current	200 A 400 V AC AC-22A IEC 200 A 400 V AC AC-23A IEC 200 A 690 V AC AC-22A IEC 200 A 690 V AC AC-23A IEC 200 A CSA 200 A UL
[Ue] rated operational voltage	600 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	750 V
Control Type	Rotary handle
Type of operating handle	External frontal External right side
Mounting Support	Plate
[Uimp] rated impulse withstand voltage	8 kV IEC
Rated power in W	100 kW 400 V 140 kW 500 V 185 kW 690 V
Rated power in hp	75 hp 240 V 92 A AC 150 hp 480 V 187 A AC 200 hp 600 V 192 A AC 15 hp 125 V 112 A DC 15 hp 250 V 56 A DC
[Icw] rated short-time withstand current	32 kA
Mechanical durability	8000 cycles
Electrical durability	6000 cycles
Connections - terminals	Lugs-ring terminals 1 0.02 in ² (16 mm ²)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	6.3 in (160 mm)
Width	7.09 in (180 mm)
Depth	3.7 in (95 mm)
Net Weight	5.03 lb(US) (2.28 kg)

Environment

Standards	IEC 60947-3 CSA C22.2 No 4 UL98
Product Certifications	UL CSA CE

Ordering and shipping details

Category	US10I1122640
Discount Schedule	0I11
GTIN	3606480510458
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.69 in (17.000 cm)
Package 1 Width	11.02 in (28.000 cm)
Package 1 Length	11.02 in (28.000 cm)
Package weight(Lbs)	5.064 lb(US) (2.297 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	15.75 in (40.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	22.148 lb(US) (10.046 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No