

# Product data sheet

Specifications



## Disconnect Switch, TeSys LK, nonfusible, 400A, 600 V, HP rated, 3 pole, rotary handle, up to 200kA SCCR

LK4QU3N

**Product availability: Stock - Normally stocked in distribution facility**

### Main

Range	TeSys
Product name	TeSys LK
Product or Component Type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes

### Complementary

Poles description	3P
Network type	AC DC
Network Frequency	50/60 Hz
[Ie] rated operational current	200 A 690 V AC AC-23A IEC 400 A 400 V AC AC-22A IEC 400 A 400 V AC AC-23A IEC 400 A 690 V AC AC-22A IEC 400 A CSA 400 A UL
[Ue] rated operational voltage	600 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	1000 V
Control Type	Rotary handle
Type of operating handle	External frontal External right side
Mounting Support	Plate
[Uimp] rated impulse withstand voltage	12 kV IEC
Rated power in W	185 kW 690 V 220 kW 400 V 280 kW 500 V
Rated power in hp	125 hp 240 V 312 A AC 250 hp 480 V 302 A AC 350 hp 600 V 336 A AC 20 hp 125 V 148 A DC 50 hp 250 V 173 A DC
[Icw] rated short-time withstand current	48 kA
Mechanical durability	6000 cycles
Electrical durability	1000 cycles
Connections - terminals	Lugs-ring terminals 1 0.02 in <sup>2</sup> (16 mm <sup>2</sup> )

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Height</b>	10.2 in (260 mm)
<b>Width</b>	9.06 in (230 mm)
<b>Depth</b>	5.04 in (128 mm)

## Environment

<b>Standards</b>	UL98 IEC 60947-3 CSA C22.2 No 4
<b>Product Certifications</b>	CE UL CSA

## Ordering and shipping details

<b>Category</b>	US10I1122640
<b>Discount Schedule</b>	0I11
<b>GTIN</b>	3606480510465
<b>Returnability</b>	Yes
<b>Country of origin</b>	FR

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	11.10 in (28.200 cm)
<b>Package 1 Width</b>	21.30 in (54.100 cm)
<b>Package 1 Length</b>	16.54 in (42.000 cm)
<b>Package weight(Lbs)</b>	14.114 lb(US) (6.402 kg)
<b>Unit Type of Package 2</b>	P12
<b>Number of Units in Package 2</b>	4
<b>Package 2 Height</b>	29.53 in (75.000 cm)
<b>Package 2 Width</b>	31.50 in (80.000 cm)
<b>Package 2 Length</b>	47.24 in (120.000 cm)
<b>Package 2 Weight</b>	82.912 lb(US) (37.608 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

### Use Again

 <b>Repack and remanufacture</b>	
Circularity Profile	No need of specific recycling operations
Take-back	No