

Product data sheet

Specifications



Reverser block for vertical mounting, TeSys Ultra, 38A/690V, coil 110-240VAC/DC

LU2MB0FU

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Device short name	LU2MB
Product or Component Type	Reverser block
Device mounting	Direct mounting
Device Application	Motor control
[Ie] rated operational current	38 A
[Uc] control circuit voltage	110...240 V AC 50/60 Hz 110...220 V DC
Current consumption	1000 mA 110...220 V DC I maximum while closing 1000 mA 110...240 V AC I maximum while closing

Complementary

[Ue] rated operational voltage	690 V AC power circuit
Network frequency	40...60 Hz
Inrush restraint duration	25 ms AC 15 ms DC
Operating time	150 ms with change of direction 75 ms without change of direction
Standards	EN 60947-6-2 IEC 60947-6-2 UL 60947-4-1, with phase barrier CSA C22.2 No 60947-4-1, with phase barrier
Product Certifications	CE UL CSA CCC EAC ASEFA ATEX Marine
[Ui] rated insulation voltage	690 V IEC 60947-6-2 600 V UL 60947-4-1 600 V CSA C22.2 No 60947-4-1
[Uimp] rated impulse withstand voltage	6 kVIEC 60947-6-2
Fixing mode	Plug-in

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Connections - terminals	Control circuit screw clamp terminals 1 0.0005...0.002 in ² (0.34...1.5 mm ²) 0.1 in (3 mm)) flexible with cable end Control circuit screw clamp terminals 1 0.001...0.002 in ² (0.75...1.5 mm ²) 0.1 in (3 mm)) flexible without cable end Control circuit screw clamp terminals 1 0.001...0.002 in ² (0.75...1.5 mm ²) 0.1 in (3 mm)) rigid Control circuit screw clamp terminals 2 0.0005...0.002 in ² (0.34...1.5 mm ²) 0.1 in (3 mm)) flexible with cable end Control circuit screw clamp terminals 2 0.001...0.002 in ² (0.75...1.5 mm ²) 0.1 in (3 mm)) flexible without cable end Control circuit screw clamp terminals 2 0.001...0.002 in ² (0.75...1.5 mm ²) 0.1 in (3 mm)) rigid Power circuit screw clamp terminals 1 0.002...0.02 in ² (1...10 mm ²) 0.2 in (4 mm)) rigid Power circuit screw clamp terminals 1 0.002...0.009 in ² (1...6 mm ²) 0.2 in (4 mm)) flexible with cable end Power circuit screw clamp terminals 1 0.004...0.02 in ² (2.5...10 mm ²) 0.2 in (4 mm)) flexible without cable end Power circuit screw clamp terminals 2 0.002...0.009 in ² (1...6 mm ²) 0.2 in (4 mm)) flexible with cable end Power circuit screw clamp terminals 2 0.002...0.009 in ² (1...6 mm ²) 0.2 in (4 mm)) rigid Power circuit screw clamp terminals 2 0.002...0.009 in ² (1.5...6 mm ²) 0.2 in (4 mm)) flexible without cable end
Tightening torque	Control circuit: 7.08...10.6 lbf.in (0.8...1.2 N.m) flat screwdriver 0.2 in (5 mm) Control circuit: 7.08...10.6 lbf.in (0.8...1.2 N.m) Philips No 2 screwdriver 0.2 in (5 mm) Power circuit: 16.8...22.1 lbf.in (1.9...2.5 N.m) flat screwdriver 0.2 in (6 mm) Power circuit: 16.8...22.1 lbf.in (1.9...2.5 N.m) Philips No 2 screwdriver 0.2 in (6 mm)
Width	1.8 in (45 mm)
Height	3.1 in (80 mm)
Depth	4.1 in (105 mm)
Net Weight	0.9 lb(US) (0.4 kg)
Compatibility code	LU2MB

Environment

IP degree of protection	IP20 IEC 60947-1 front panel and wired terminals) IP20 IEC 60947-1 other faces) IP40 IEC 60947-1 front panel outside connection zone)
Protective treatment	TH IEC 60068
Ambient air temperature for operation	-13...140 °F (-25...60 °C) with LUCM -13...158 °F (-25...70 °C) with LUCA, LUCB, LUCC, LUCD
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Fire resistance	1760 °F (960 °C) parts supporting live components IEC 60695-2-12 1202 °F (650 °C) IEC 60695-2-12
Operating altitude	6561.68 ft (2000 m)
Shock resistance	10 gn power poles open IEC 60068-2-27 15 gn power poles closed IEC 60068-2-27
Vibration resistance	2 gn 5...300 Hz) power poles open IEC 60068-2-27 4 gn 5...300 Hz) power poles closed IEC 60068-2-27
Resistance to electrostatic discharge	8 kV level 3, in open air IEC 61000-4-2 8 kV level 4, on contact IEC 61000-4-2
Resistance to radiated fields	9.1 V/m (10 V/m) level 3 IEC 61000-4-3
Resistance to fast transients	2 kV 3 serial link IEC 61000-4-4 4 kV 4 all circuits except for serial link IEC 61000-4-4
Non-dissipating shock wave	1 kV serial mode IEC 60947-6-2 2 kV common mode IEC 60947-6-2
Immunity to radioelectric fields	10 V IEC 61000-4-6

Ordering and shipping details

Category	US10I1122399
Discount Schedule	0I11
GTIN	3389110363807
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.2 in (5.7 cm)
Package 1 Width	3.7 in (9.5 cm)
Package 1 Length	5.1 in (13.0 cm)
Package weight(Lbs)	14.0 oz (396.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	11.129 lb(US) (5.048 kg)

Contractual warranty

Warranty	18 months
----------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 4

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number Ea04e023-7196-4d5e-a41f-a711a93b86d7

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**

PVC free Yes

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.