Product data sheet

Specifications

Pre-wired shunt trip release MX, ComPacT NSXm, 24VDC, 24VAC 50/60Hz

LV426861

Main

Range	ComPact
Range of product	ComPacT NSXm
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Opening coil Shunt trip release
Control type	Standard
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC
Range compatibility	ComPact ComPacT NSXm ComPact ComPact NSXm PowerPact PowerPact B

Complementary

Operating threshold	0.7 Un opening
Response time	< 50 ms
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Auxiliary connection terminal	Pre-wired 0…0.8 mm² (AWG 18)stranded copper
Wire stripping length	8 mm
Cable length	1 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.1 cm
Package 1 Length	8.3 cm
Package 1 Weight	80 g
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Height	30 cm

Life Is On | Schneider Electric

Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1.927 kg

Life Is On | Schneider Electric

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained ›

How we assess product sustainability ›

Environmental footprint

Total lifecycle Carbon footprint	**2**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant with Exemptions**
SCIP Number	**75582d60-9779-4641-a03b-18e996230a58**
REACh Regulation	**REACh Declaration**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
Halogen-free status	**Product contains halogen above thresholds**
Silicone-free	**No**

Use Again

Repack and remanufacture

End of life manual availability	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**