

Product data sheet

Specifications



Circuit breaker accessory, PowerPacT B, terminal shield, long

LV426911

Product availability: Stock - Normally stocked in distribution facility

Main

Range compatibility	ComPact ComPacT NSXm ComPact ComPact NSXm PowerPact PowerPact B
Product or Component Type	Long terminal shield

Complementary

Accessory / separate part category	Insulation accessory
Accessory / Separate Part Type	Insulation accessories
Poles description	2P
Quantity per Set	Set of 1
Location of connection	Upstream Downstream
Line Rated Current	16...160 A
IP degree of protection	IP40 conforming to IEC 60529

Ordering and shipping details

Category	US10DE201136
Discount Schedule	0DE2
GTIN	3606485444253
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.35 in (8.500 cm)
Package 1 Width	2.80 in (7.100 cm)
Package 1 Length	2.44 in (6.200 cm)
Package weight(Lbs)	2.698 oz (76.500 g)
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	5.721 lb(US) (2.595 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds

Use Again

 Repack and remanufacture	
Take-back	No

Offer Marketing Illustration

Product benefits / Features



Compact NSX Technical Benefits

- Come in one size and are optimized for small spaces.
- 3 or 4 pole versions
- Rated currents: 16 to 160 A
- Thermal-magnetic protections
- Breaking capacities under 240/415 V
16, 25, 36, 50, 70 kA
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- EverLink™ connectors for bare cables

Offer Marketing Illustration

Product benefits / Features



Compact NSXm
Range Accessories

Wireless indication auxiliary

Long terminal shield

Standard auxiliary contact

Rotary handles

Inter-phase barrier

Toggle padlocking device

MN undervoltage release

Standard MX shunt release

The image displays a collection of accessories for the Compact NSXm circuit breaker range. It includes a wireless indication auxiliary, a long terminal shield, a standard auxiliary contact, rotary handles, an inter-phase barrier, a toggle padlocking device, an MN undervoltage release, and a standard MX shunt release. Each accessory is shown with a small image and a corresponding label.

Offer Marketing Illustration

Product benefits / Features

CompacT NSXm Moulded Case Circuit Breaker



Efficiency

It features integrated earth leakage protection and standardized accessories – which means you save space, time, and effort.



Reliability

optimized in size and featuring innovations tailored to your needs. Roto-active™ breaking technology helps to increase operation lifespan.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.

