

Product data sheet

Specifications



Long terminal shield, ComPact NSXm, upstream and downstream mounting, IP40, 3 poles

LV426912

Main

Range compatibility ComPact ComPact NSXm
PowerPact PowerPact B

Product or component type Long terminal shield

Complementary

Accessory / separate part type Insulation accessories

Poles description 3P

Quantity per set Set of 1

Location of connection Upstream
Downstream

Connection pitch 35 mm

IP degree of protection IP40 conforming to IEC 60529

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 7.400 cm

Package 1 Width 8.800 cm

Package 1 Length 9.100 cm

Package 1 Weight 106.000 g

Unit Type of Package 2 S03

Number of Units in Package 2 45

Package 2 Height 30.000 cm

Package 2 Width 30.000 cm

Package 2 Length 40.000 cm

Package 2 Weight 5.302 kg

Unit Type of Package 3 P12

Number of Units in Package 3 720

Package 3 Height 75.000 cm

Package 3 Width 80.000 cm

Package 3 Length 120.000 cm

Package 3 Weight 100.000 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen-free status	Product contains halogen above thresholds

Use Again

 Repack and remanufacture	
Take-back	No