

# Product data sheet

Specifications



standard auxiliary contact, ComPact NSXm, circuit breaker status OF/SD, 1 changeover contact type

LV426950

## Main

Product or component type	Auxiliary contact
Device short name	SD OF
Device application	Breaker status monitoring
Range compatibility	PowerPact PowerPact B ComPact ComPact NSXm
Signal contacts composition	1 NO/NC

## Complementary

Fault type	Overload Short-circuit
Local signalling	ON/OFF indication for open/close Trip indicator for relay trip indicator
Auxiliary contacts type	Standard
Mounting mode	Clip-on
[I <sub>th</sub> ] conventional free air thermal current	5 A
Breaking capacity (A)	AC-12: 5 A at 24 V AC 50/60 Hz AC-12: 5 A at 48 V AC 50/60 Hz AC-12: 5 A at 110...127 V AC 50/60 Hz AC-12: 5 A at 220/240 V AC 50/60 Hz AC-12: 5 A at 380/440 V AC 50/60 Hz AC-12: 5 A at 660/690 V AC 50/60 Hz AC-15: 5 A at 24 V AC 50/60 Hz AC-15: 5 A at 48 V AC 50/60 Hz AC-15: 4 A at 110...127 V AC 50/60 Hz AC-15: 3 A at 220/240 V AC 50/60 Hz AC-15: 2.5 A at 380/440 V AC 50/60 Hz AC-15: 0.1 A at 660/690 V AC 50/60 Hz DC-12: 5 A at 24 V DC 50/60 Hz DC-12: 2.5 A at 48 V DC 50/60 Hz DC-12: 0.6 A at 110 V DC 50/60 Hz DC-12: 0.3 A at 250 V DC DC-13: 2.5 A at 24 V DC DC-13: 1.2 A at 48 V DC DC-13: 0.35 A at 110 V DC DC-13: 0.05 A at 250 V DC DC-14: 1 A at 24 V DC DC-14: 0.2 A at 48 V DC DC-14: 0.05 A at 110 V DC DC-14: 0.03 A at 250 V DC
Minimum load	2 mA at 17 V DC
Auxiliary connection terminal	Spring
Wire stripping length	8 mm for front connection

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	1.200 cm
<b>Package 1 Width</b>	7.500 cm
<b>Package 1 Length</b>	10.500 cm
<b>Package 1 Weight</b>	25.000 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	5.000 cm
<b>Package 2 Width</b>	14.000 cm
<b>Package 2 Length</b>	25.000 cm
<b>Package 2 Weight</b>	257.000 g
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	220
<b>Package 3 Height</b>	30.000 cm
<b>Package 3 Width</b>	30.000 cm
<b>Package 3 Length</b>	40.000 cm
<b>Package 3 Weight</b>	6.300 kg



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 2

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Use Again

### Repack and remanufacture

End of life manual availability No need of specific recycling operations

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins