

Product data sheet

Specifications



LXM52 single drive 10A/30A

LXM52DD30C41000

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	PacDrive 3
Device short name	LXM 52
Product or Component Type	Single drive
Product compatibility	Servo motor SH3 3.9 in (100 mm), 3 optimized in terms of torque and speed Servo motor SH3 3.9 in (100 mm), 4 optimized in terms of torque and speed Servo motor SH3 5.5 in (140 mm), 1 optimized in terms of torque and speed Servo motor MH3 3.9 in (100 mm), 3 optimized in terms of torque and speed Servo motor MH3 5.5 in (140 mm), 1 optimized in terms of torque and speed
Component name	LXM52

Complementary

Phase	Three phase
[Us] rated supply voltage	208...480 V - 15...10 %
Supply frequency	50...60 Hz - 5...5 %
Continuous output current	10 A 8 kHz
Output current 3s peak	30 A
Continuous power	5.6 kW
Nominal power	3 kW
Switching frequency	8 kHz
Overvoltage category	III
Electrical connection	Terminal 0.75...5.3 mm ² , AWG 18...AWG 10 CN1) Terminal 0.75...5.3 mm ² , AWG 18...AWG 10 CN10)
Tightening torque	CN1 6.02 lbf.in (0.68 N.m) CN10 6.02 lbf.in (0.68 N.m)
Number of inputs	4 digital 4 touch probe
Discrete input voltage	24 V DC
Number of outputs	2 digital
Discrete output voltage	24 V DC
Contact bounce time	> 1 ms compliment of STO_A, compliment of STO_B
Communication interface	SERCOS III, Integrated
Width	2.7 in (68 mm)
Height	10.6 in (270 mm)
Depth	8.5 in (217 mm)
Net Weight	6.0 lb(US) (2.7 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Standards	IEC 61800-3 IEC 61800-5-1
Product Certifications	CE UL
IP degree of protection	IP20 IEC 60721-3-3
Vibration resistance	10 m/s ² conforming to IEC 60721-3-3
Shock resistance	100 m/s ² IEC 60721-3-3
Pollution degree	2
Environmental characteristic	3K3 conforming to IEC 60721-3-3
Relative humidity	5...95 %
Ambient Air Temperature for Operation	32...122 °F (0...50 °C)

Ordering and shipping details

Category	US1PC5218355
Discount Schedule	PC52
GTIN	3606480517327
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.331 in (11.000 cm)
Package 1 Width	10.827 in (27.500 cm)
Package 1 Length	12.992 in (33.000 cm)
Package weight(Lbs)	7.300 lb(US) (3.311 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	16.195 lb(US) (7.346 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	16
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	151.608 lb(US) (68.768 kg)

Contractual warranty

Warranty	18 months
----------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 5241

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number 3d0be293-7e12-47d2-b52f-e501202c4302

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

PVC free Yes

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No