

Product data sheet

Specifications



Lexium 62 Double Drive - 6 A - accessory kit included

LXM62DU60D21000

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	PacDrive 3
Device short name	LXM 62
Product or Component Type	Double drive
Component name	LXM62

Complementary

Product compatibility	Servo motor SHS Servo motor SH3 2.2 in (55 mm), 1 optimized in terms of torque and speed Servo motor SH3 2.2 in (55 mm), 2 optimized in terms of torque and speed Servo motor SH3 2.2 in (55 mm), 3 optimized in terms of torque and speed Servo motor SH3 2.8 in (70 mm), 1 optimized in terms of torque and speed Servo motor SH3 2.8 in (70 mm), 2 optimized in terms of high torque Servo motor SH3 2.8 in (70 mm), 3 optimized in terms of high torque Servo motor SH3 3.9 in (100 mm), 1 optimized in terms of high torque Servo motor MH3 2.8 in (70 mm), 1 optimized in terms of torque and speed
Phase	Three phase
[Us] rated supply voltage	400 V - 10...10 %)three phase 230 V - 10...10 %)three phase 230 V - 10...10 %)single phase
Supply frequency	50/60 Hz - 5...5 %
Continuous output current	2 A 4 kHz
Output current 3s peak	6 A 4 kHz
Continuous power	0.95 kW
Nominal power	0.95 kW
Switching frequency	8 kHz
Overvoltage category	III
Electrical connection	Terminal 0.2...15 mm ² , AWG 24...AWG 16 CN4) Terminal 0.5...16 mm ² , AWG 20...AWG 6 CN5) Terminal 0.75...16 mm ² , AWG 18...AWG 6 CN6) Terminal 0.2...6 mm ² , AWG 24...AWG 10 CN7)
Tightening torque	CN1 22.1 lbf.in (2.5 N.m)
Number of inputs	2 digital 2 touch probe
Discrete input voltage	24 V DC for - 20...25 %
Number of outputs	2 digital
Discrete output voltage	24 V DC
Safety function	STO (safe torque off)
Communication interface	SERCOS III, Integrated

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Depth	10.6 in (270 mm)
Height	12.2 in (310 mm)
Width	1.8 in (44.5 mm)
Net Weight	6.6 lb(US) (3 kg)

Environment

Standards	ISO 13849-2 CSA C22.2 No 14 ISO 13849-1 IEC 62061 UL 508C IEC 61800-5-1 IEC 61800-5-2 IEC 61508 IEC 61800-3
Product Certifications	CSA CE EAC UL TÜV
IP degree of protection	IP20 IEC 60529
Vibration resistance	10 m/s ² conforming to IEC 60721-3-3
Shock resistance	100 m/s ² IEC 60721-3-3
Pollution degree	2 IEC 61800-5-2
Environmental characteristic	3K3 conforming to IEC 60721-3-3
Relative humidity	5...85 %
Ambient Air Temperature for Operation	41...131 °F (5...55 °C)

Ordering and shipping details

Category	US1PC5218356
Discount Schedule	PC52
GTIN	3606485317786
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.33 in (11.000 cm)
Package 1 Width	13.19 in (33.500 cm)
Package 1 Length	17.32 in (44.000 cm)
Package weight(Lbs)	8.792 lb(US) (3.988 kg)
Unit Type of Package 2	S06
Number of Units in Package 2	10
Package 2 Height	29.53 in (75.000 cm)
Package 2 Width	23.62 in (60.000 cm)
Package 2 Length	31.50 in (80.000 cm)

Package 2 Weight

144.738 lb(US) (65.652 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number 60beca05-ce1c-43ef-b5f4-b7c0f3eb7d27

REACH Regulation [REACH Declaration](#)

California proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](#)

PVC free Yes

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No