



## Main

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                     | Multi9                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Product name              | Multi9 C60                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Product or Component Type | Miniature circuit-breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Device short name         | C60SP                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Device Application        | Distribution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Poles description         | 1P                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Number of protected poles | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Line Rated Current        | 16 A 77 °F (25 °C) EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Network type              | DC<br>AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Trip unit technology      | Thermal-magnetic                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Curve code                | D                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Breaking capacity         | 10 KA AIR 277 V AC UL 1077<br>14 KA AIR 240 V AC UL 1077<br>14 KA AIR 120 V AC UL 1077<br>10 KA AIR 65 V DC UL 1077<br>10 KA AIR 277 V AC CSA C22.2 No 235<br>14 KA AIR 240 V AC CSA C22.2 No 235<br>14 KA AIR 120 V AC CSA C22.2 No 235<br>10 KA AIR 65 V DC CSA C22.2 No 235<br>3 KA Icu 415 V AC EN/IEC 60947-2<br>10 KA Icu 240 V AC EN/IEC 60947-2<br>20 KA Icu 60 V DC EN/IEC 60947-2<br>3 KA Icu 415 V AC GB 14048.2<br>10 KA Icu 240 V AC GB 14048.2<br>20 KA Icu 60 V DC GB 14048.2 |
| Suitability for isolation | Yes EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Standards                 | EN/IEC 60947-2<br>GB 14048.2<br>UL 1077<br>CSA C22.2 No 235                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Product certifications    | IEC[RETURN]CCC[RETURN]UR[RETURN]CSA                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

## Complementary

|                                        |                                                                                                                                                                                                                                        |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ue] rated operational voltage         | 240 V AC 50/60 Hz<br>415 V AC 50/60 Hz<br>60 V DC                                                                                                                                                                                      |
| Magnetic tripping limit                | 12 x In +/- 20 % AC<br>17 x In +/- 20 % DC                                                                                                                                                                                             |
| [Ics] rated service breaking capacity  | 2.25 KA 75 % EN/IEC 60947-2 - 415 V AC<br>7.5 KA 75 % EN/IEC 60947-2 - 240 V AC<br>20 KA 100 % EN/IEC 60947-2 - 60 V DC<br>2.25 KA 75 % GB 14048.2 - 415 V AC<br>7.5 KA 75 % GB 14048.2 - 240 V AC<br>20 KA 100 % GB 14048.2 - 60 V DC |
| [Ui] rated insulation voltage          | 500 V AC EN/IEC 60947-2                                                                                                                                                                                                                |
| [Uimp] rated impulse withstand voltage | 6 kVEN/IEC 60947-2                                                                                                                                                                                                                     |
| Contact position indicator             | Yes                                                                                                                                                                                                                                    |
| Control Type                           | Toggle                                                                                                                                                                                                                                 |
| Local signalling                       | ON/OFF indication                                                                                                                                                                                                                      |
| Mounting Mode                          | Clip-on                                                                                                                                                                                                                                |

|                          |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mounting Support         | DIN rail                                                                                                                                                                                                                                                                                                                                                                          |
| 9 mm pitches             | 2                                                                                                                                                                                                                                                                                                                                                                                 |
| Height                   | 3.2 in (81 mm)                                                                                                                                                                                                                                                                                                                                                                    |
| Width                    | 0.7 in (18 mm)                                                                                                                                                                                                                                                                                                                                                                    |
| Depth                    | 2.8 in (72 mm)                                                                                                                                                                                                                                                                                                                                                                    |
| Color                    | Gray                                                                                                                                                                                                                                                                                                                                                                              |
| Mechanical durability    | 20000 cycles                                                                                                                                                                                                                                                                                                                                                                      |
| Electrical durability    | 10000 cycles                                                                                                                                                                                                                                                                                                                                                                      |
| Provision for padlocking | Padlockable                                                                                                                                                                                                                                                                                                                                                                       |
| Connections - terminals  | Tunnel type terminal top or bottom) 0.002...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) AWG 18...AWG 8) - rigid<br>Tunnel type terminal top or bottom) 0.002...0.02 in <sup>2</sup> (1...16 mm <sup>2</sup> ) AWG 18...AWG 8) - flexible with ferrule<br>Tunnel type terminal top or bottom) 0.002...0.02 in <sup>2</sup> (1...16 mm <sup>2</sup> ) AWG 18...AWG 8) - flexible |
| Wire stripping length    | 0.6 in (14 mm) for top or bottom connection                                                                                                                                                                                                                                                                                                                                       |
| Tightening torque        | 22.1 lbf.in (2.5 N.m) top or bottom                                                                                                                                                                                                                                                                                                                                               |
| Earth-leakage protection | Without                                                                                                                                                                                                                                                                                                                                                                           |

## Environment

|                                       |                                                                                  |
|---------------------------------------|----------------------------------------------------------------------------------|
| IP degree of protection               | IP20 conforming to IEC 60529<br>IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree                      | 3 EN/IEC 60947-2                                                                 |
| Tropicalisation                       | 2 IEC 60068-1                                                                    |
| Relative humidity                     | 95 % 131 °F (55 °C)                                                              |
| Operating altitude                    | 0...6561.68 ft (0...2000 m)                                                      |
| Ambient air temperature for operation | -22...158 °F (-30...70 °C)                                                       |
| Ambient Air Temperature for Storage   | -40...176 °F (-40...80 °C)                                                       |

## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10DE200948  |
| Discount Schedule | 0DE2          |
| GTIN              | 3606481168795 |
| Returnability     | Yes           |
| Country of origin | FR            |

## Packing Units

|                              |                           |
|------------------------------|---------------------------|
| Unit Type of Package 1       | PCE                       |
| Number of Units in Package 1 | 1                         |
| Package 1 Height             | 0.7 in (1.8 cm)           |
| Package 1 Width              | 3.0 in (7.5 cm)           |
| Package 1 Length             | 3.3 in (8.5 cm)           |
| Package 1 Weight             | 4.0 oz (112.0 g)          |
| Unit Type of Package 2       | BB1                       |
| Number of Units in Package 2 | 12                        |
| Package 2 Height             | 3.0 in (7.6 cm)           |
| Package 2 Width              | 3.5 in (8.8 cm)           |
| Package 2 Length             | 8.9 in (22.5 cm)          |
| Package 2 Weight             | 3.051 lb(US) (1.384 kg)   |
| Unit Type of Package 3       | S03                       |
| Number of Units in Package 3 | 144                       |
| Package 3 Height             | 11.8 in (30.0 cm)         |
| Package 3 Width              | 11.8 in (30.0 cm)         |
| Package 3 Length             | 15.7 in (40.0 cm)         |
| Package 3 Weight             | 37.767 lb(US) (17.131 kg) |

## Offer Sustainability

|                             |                                                                                                                                 |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status    | Green Premium product                                                                                                           |
| REACH Regulation            | <a href="#"> REACH Declaration</a>             |
| EU RoHS Directive           | Compliant with Exemptions                                                                                                       |
| Mercury free                | Yes                                                                                                                             |
| China RoHS Regulation       | <a href="#"> China RoHS Declaration</a>        |
| RoHS exemption information  | <a href="#"> Yes</a>                           |
| Environmental Disclosure    | <a href="#"> Product Environmental Profile</a> |
| Circularity Profile         | No need of specific recycling operations                                                                                        |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.    |
| Halogen content performance | Halogen free product                                                                                                            |