



## Main

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                     | Multi9                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Product name              | Multi9 C60                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Product or Component Type | Miniature circuit-breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Device short name         | C60BPR                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Device Application        | Distribution                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Poles description         | 1P                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Number of protected poles | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Line Rated Current        | 8 A 77 °F (25 °C) EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Network type              | AC<br>DC                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Trip unit technology      | Thermal-magnetic                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Curve code                | C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Breaking capacity         | 3 KA Icu 415 V AC EN/IEC 60947-2<br>10 KA Icu 240 V AC EN/IEC 60947-2<br>20 KA Icu 60 V DC EN/IEC 60947-2<br>3 KA Icu 415 V AC GB 14048.2<br>10 KA Icu 240 V AC GB 14048.2<br>20 KA Icu 60 V DC GB 14048.2<br>10 KA AIR 277 V AC UL 489<br>14 KA AIR 240 V AC UL 489<br>14 KA AIR 120 V AC UL 489<br>10 KA AIR 60 V DC UL 489<br>10 KA AIR 277 V AC CSA C22.2 No 5<br>14 KA AIR 240 V AC CSA C22.2 No 5<br>14 KA AIR 120 V AC CSA C22.2 No 5<br>10 KA AIR 60 V DC CSA C22.2 No 5 |
| Suitability for isolation | Yes EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Standards                 | EN/IEC 60947-2<br>GB 14048.2<br>UL 489<br>CSA C22.2 No 5                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Product certifications    | IEC[RETURN]CCC[RETURN]CSA[RETURN]UL                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## Complementary

|                                        |                                                                                                                                                                                                                                      |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ue] rated operational voltage         | 240 V AC 50/60 Hz<br>415 V AC 50/60 Hz<br>60 V DC                                                                                                                                                                                    |
| Magnetic tripping limit                | 8.5 x In +/- 20 % AC<br>12 x In +/- 20 % DC                                                                                                                                                                                          |
| [Ics] rated service breaking capacity  | 2.25 KA 75 % EN/IEC 60947-2 - 415 V AC<br>7.5 KA 75 % EN/IEC 60947-2 - 240 V AC<br>2.25 KA 75 % GB 14048.2 - 415 V AC<br>7.5 KA 75 % GB 14048.2 - 240 V AC<br>15 KA 75 % GB 14048.2 - 60 V DC<br>15 KA 75 % EN/IEC 60947-2 - 60 V DC |
| [Ui] rated insulation voltage          | 500 V AC EN/IEC 60947-2                                                                                                                                                                                                              |
| [Uimp] rated impulse withstand voltage | 6 kVEN/IEC 60947-2                                                                                                                                                                                                                   |
| Contact position indicator             | Yes                                                                                                                                                                                                                                  |
| Control Type                           | Toggle                                                                                                                                                                                                                               |
| Local signalling                       | ON/OFF indication                                                                                                                                                                                                                    |
| Mounting Mode                          | Clip-on                                                                                                                                                                                                                              |

|                          |                                   |
|--------------------------|-----------------------------------|
| Mounting Support         | DIN rail                          |
| 9 mm pitches             | 2                                 |
| Height                   | 5.0000000000 in (127 mm)          |
| Width                    | 0.7 in (18 mm)                    |
| Depth                    | 2.8 in (72 mm)                    |
| Color                    | Gray                              |
| Mechanical durability    | 20000 cycles                      |
| Electrical durability    | 10000 cycles                      |
| Provision for padlocking | Padlockable                       |
| Connections - terminals  | Ring terminal top or bottom)      |
| Tightening torque        | 17.7 lbf.in (2 N.m) top or bottom |
| Earth-leakage protection | Without                           |

## Environment

|                                       |                                                                                  |
|---------------------------------------|----------------------------------------------------------------------------------|
| IP degree of protection               | IP20 conforming to IEC 60529<br>IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree                      | 3 EN/IEC 60947-2                                                                 |
| Overvoltage category                  | IV                                                                               |
| Tropicalisation                       | 2 IEC 60068-1                                                                    |
| Relative humidity                     | 95 % 131 °F (55 °C)                                                              |
| Operating altitude                    | 0...6561.68 ft (0...2000 m)                                                      |
| Ambient air temperature for operation | -22...158 °F (-30...70 °C)                                                       |
| Ambient Air Temperature for Storage   | -40...176 °F (-40...80 °C)                                                       |

## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10DE200949  |
| Discount Schedule | 0DE2          |
| GTIN              | 3606481170804 |
| Returnability     | Yes           |
| Country of origin | FR            |

## Packing Units

|                              |                             |
|------------------------------|-----------------------------|
| Unit Type of Package 1       | PCE                         |
| Number of Units in Package 1 | 1                           |
| Package 1 Height             | 2.953 in (7.500 cm)         |
| Package 1 Width              | 0.709 in (1.800 cm)         |
| Package 1 Length             | 5.0000000000 in (12.700 cm) |
| Package 1 Weight             | 5.150 oz (146.000 g)        |
| Unit Type of Package 2       | BB1                         |
| Number of Units in Package 2 | 12                          |
| Package 2 Height             | 3.150 in (8.000 cm)         |
| Package 2 Width              | 8.661 in (22.000 cm)        |
| Package 2 Length             | 5.197 in (13.200 cm)        |
| Package 2 Weight             | 4.008 lb(US) (1.818 kg)     |
| Unit Type of Package 3       | S03                         |
| Number of Units in Package 3 | 96                          |
| Package 3 Height             | 11.811 in (30.000 cm)       |
| Package 3 Width              | 11.811 in (30.000 cm)       |
| Package 3 Length             | 15.748 in (40.000 cm)       |
| Package 3 Weight             | 33.045 lb(US) (14.989 kg)   |

## Offer Sustainability

|                             |                                                                                                                                 |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status    | Green Premium product                                                                                                           |
| REACH Regulation            | <a href="#"> REACH Declaration</a>             |
| EU RoHS Directive           | Compliant with Exemptions                                                                                                       |
| Mercury free                | Yes                                                                                                                             |
| China RoHS Regulation       | <a href="#"> China RoHS Declaration</a>        |
| RoHS exemption information  | <a href="#"> Yes</a>                           |
| Environmental Disclosure    | <a href="#"> Product Environmental Profile</a> |
| Circularity Profile         | No need of specific recycling operations                                                                                        |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.    |
| Halogen content performance | Halogen free product                                                                                                            |