


Product data sheet

Specifications



Add-on residual current device,
Multi9 Vigi C60, 3P, 63A, AC type,
instantaneous, 30mA, 400/415VAC

M9V11363

Product availability: Non-Stock - Not normally stocked in
distribution facility

Main

Range	Multi9
Product or Component Type	Add-on residual current device
Device short name	Vigi C60
Range compatibility	Multi9 Multi9 C60 C60N Multi9 Multi9 C60 C60L Multi9 Multi9 C60 C60H Multi9 Multi9 C60 C60CTRL
Poles description	3P
Line Rated Current	63 A EN/IEC 61009-1
Network type	AC
Network Frequency	50 Hz
[Ue] rated operational voltage	400/415 V AC 50 Hz
Earth-leakage sensitivity	30 mA EN/IEC 61009-1
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type AC
9 mm pitches	7
Standards	EN/IEC 61009-1 EN/IEC 61009-2-1

Complementary

Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	500 V AC 50 Hz EN/IEC 61009-1
[Uimp] rated impulse withstand voltage	4 kVEN/IEC 61009-1
Local signalling	Fault indication
Mounting Mode	Clip-on
Mounting Support	DIN rail
Electrical connection to mcb	By screws
Height	3.4 in (87 mm)
Width	2.5 in (63 mm)
Depth	2.9 in (74 mm)
Net Weight	7.4 oz (210 g)
color	Gray

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - terminals	Tunnel type terminal bottom) 0.002...0.05 in² (1...35 mm²) - rigid Tunnel type terminal bottom) 0.002...0.04 in² (1...25 mm²) - flexible Tunnel type terminal bottom) 0.002...0.04 in² (1...25 mm²) - flexible with ferrule
Wire stripping length	0.6 in (14 mm) for bottom connection
Tightening torque	31.0 lbf.in (3.5 N.m) bottom

Environment

IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	3 IEC 61009
Electromagnetic compatibility	8/20 µs impulse withstand, 250 A EN/IEC 61009-1
Tropicalisation	2 IEC 60068-1
Relative humidity	95 % 131 °F (55 °C)
Ambient air temperature for operation	23...140 °F (-5...60 °C)
Ambient Air Temperature for Storage	-40...140 °F (-40...60 °C)

Ordering and shipping details

Category	US10DE200908
Discount Schedule	0DE2
GTIN	3606480684555
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.425 in (8.700 cm)
Package 1 Width	4.724 in (12.000 cm)
Package 1 Length	5.827 in (14.800 cm)
Package weight(Lbs)	9.206 oz (261.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	15
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	9.678 lb(US) (4.390 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	121
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	01327915-acdb-4543-8666-60c841ff9e81
REACH Regulation	REACH Declaration

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.